

German Hoses for Fume / Flue Gas Collection



+91-99 784 42 215
+91-90 990 16 044



flexaflexhoses@gmail.com
flexaflex.ahd@gmail.com



+91-79 - 22 14 0461
+91-79 - 22 16 1360



www.flexaflexhoses.com

FLEXAFLEX HOSES INTERNATIONAL
106, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkva Gate,
Ahmedabad - 380 002



Wall Thick. 0.4 mm
Temp. : 90°C / 125°C
PU HOSE - LIGHT DUTY



Wall Thick. 0.6 & 0.7 mm
Temp. : 90°C / 125°C
PU HOSE - HEAVY DUTY



Wall Thick. 0.4, 0.6, 0.7, 1.4 & 2 mm
Temp. : 90°C / 125°C
Smartflex PU Hose
Permanently Antistatic / Flame Retardant



Wall Thick. 0.5 / 0.6 & 1 mm
Temp. : 310°C
SILICON DOUBLE LAYER HOSE



Temp. : 135°C / 150°C
TPR HOSE (Thermoplastic Rubber)



Temp. : 80°C
PVC Coated Polyester Fabric Hose - Blue



Light
Temp. : 80°C
PVC Coated Polyester Fabric Hose - Grey



Fire Retardant
Temp. : 80°C
PVC Coated Polyester Fabric Hose - Black



Temp. : 60°C
PVC Duct Hose - Grey



Temp. : 300°C
High Temperature Clip Silicon Hose



Temp. : 300°C
Kevlar- Silicon CL Hose



Temp. : 250°C
PTFE - Teflon CL Hose



Temp. : 450°C to 1100°C
High Temp. Clip Hose



Temp. : 210°C
PTFE with SS Braiding



Temp. : 400°C / 600°C
SS Corrugated Hose



Temp. : 250°C
Aluminium Semi-rigid Air Duct



Temp. : 100°C / 250°C
Non-Insulated Aluminium Flexible Air Ducts



Temp. : 150°C
Insulated Aluminium Flexible Air Ducts



Alum + Polyester + PVC
Temp. : 150°C
Industrial Reinforced PVC Flexible Air Ducts



Temp. : 80°C
PP Air Hose