

German Hoses for Wood Industry



+91-99 784 42 215
+91-90 990 16 044

flexaflexhoses@gmail.com
flexaflex.ahd@gmail.com

+91-79 - 22 14 0461
+91-79 - 22 16 1360

www.flexaflexhoses.com

FLEXAFLEX HOSES INTERNATIONAL
106, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkva Gate,
Ahmedabad - 380 002



Wall Thick. 0.4 mm
Temp. : 90°C / 125°C
PU Hose - Light Duty



Wall Thick. 0.6 / 0.7 / 1 mm
Temp. : 90°C / 125°C
PU Hose - Heavy Duty



Wall Thick. 1.2 mm & 1.4 mm
Temp. : 90°C / 125°C
PU Hose - Extra Heavy Duty



Wall Thick. 0.4 / 0.6 / 0.7 / 1.4 & 2 mm
Temp. : 90°C / 125°C
Smartflex PU Hose
Permanently Antistatic / Flame Retardant



Temp. : 80°C
PU Hose With Rigid Helix



Temp. : 80°C
PU Hose With Rigid Helix
(Antistatic Copper Wire)



Temp. : 70°C
PVC Steel Wire Hose
Phthalate Free



Temp. : 65°C
PVC Steel wire Hose with Fabric Reinforced




Size : 6 mm to 76 mm
Temp. : 70°C
PVC Braided Hose



Temp. : 65°C
PVC Heavy Suction Hose With Fabric Reinforced



Temp. : 60°C
PVC Duct Hose - Grey



Temp. : 60°C
Vacuum Cleaner Hose (EVA)



Temp. : 60°C
Vacuum Cleaner Hose (EVA)
Antistatic / Conductive



For Dry / Wet
Temp. : 85°C
VAT-Elastic Hose



Temp. : 60°C
PU Tube & Fittings



S S & M S Hose Clamp