

### Flame Retardant / Antistatic Permanently Antistatic / Electrically Conductive



**PU HOSE  
PERMANENTLY ANTISTATIC  
AND FLAME RETARDANT**

**Flexadux PU ECO AS SE**

Wall Thick - 0.4 / 0.6 / 0.7 / 1 / 1.4 / 2

Temp.: -40° C up to +100 ° C



**SMARTFLEX® POLYURETHANE  
HOSE**

**FLAME RETARDANT AND  
PERMANENTLY ANTISTATIC**

Wall Thick - 0.4 / 0.6 / 0.7 / 1 / 1.4 / 2

Temp.: -40 up to + 100 ° C



**PVC STEEL WIRE HOSE**

**THUNDER HOSE  
FOOD GRADE - PHTHALATE FREE**

Wall Thick. 3.5 to 7 mm

Temp. : 70°C



**PVC SUCTION & DELIVERY  
FOOD GRADE HOSE**

**FLEXANT  
FOOD GRADE - PHTHALATE FREE - ANT**

Wall Thick. : 3 to 6.5 mm

Temp. : 60°C



**PVC NON TOXIC SUCTION HOSE  
WITH ANT COPPER WIRE**

**FOOD GRADE**

W. P. 3.5kg/cm<sup>2</sup> to 7kg/cm<sup>2</sup>

B. P. 11kg/cm<sup>2</sup> to 23kg/cm<sup>2</sup>

Temp. 60°C



**PU HOSE WITH RIGID HELIX  
Serie 3PUR M - AL - ANT**

**FOOD GRADE / ANTISTATIC**

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C




**PU HOSE  
ELECTRICALLY CONDUCTIVE**

**Flexadux P7 M PU EL**

Wall Thick. : 1.4 mm

Temp. : -40° up to +100° C



**POLYURETHANE HOSE - FLAT**

**Flexadux P7 L PU AE  
Flat - Food Grade**

Wall Thick. : 0.7 mm

Temp.: -40° C up to +100 ° C



**HDPE SEMI RIGID SELF  
SUPPORTING HOSE  
CONDUCTIVE HOSE (EL)**

Temp. : -20°C to +70°C



**FDA-GRADE CHEMICAL  
HOSE  
UHMWPE**

Range : 19 mm to 102 mm ID

W.P. 16 kg/cm<sup>2</sup>

Temp. -25°C to 100°C


Steam Cleaning upto +130°C ( for Max 30 Minutes)



**LONGWALL MINE HOSE**  
Two Steel Braided  
**MSHA**  
Range : 63.5 mm & 76.2 mm  
**W.P. 69 kg/cm<sup>2</sup>**  
**B.P. 276 kg/cm<sup>2</sup>**  
Temp. -40°C to +100°C



**SAND BLAST HOSE**  
**SHOT BLAST HOSE**  
Range : 20 mm to 75 mm ID  
**W.P. 7 / 10 / 12 kg/cm<sup>2</sup>**  
Temp. -40°C to +70°C  
IS 5894 : 1980 Type I and Type II



**XLPE CHEMICAL HOSE**  
**SOLVENT HANDLING HOSE**  
Range : 25 mm to 50 mm ID  
**W.P. 14 kg/cm<sup>2</sup>**  
Temp. -30°C to 90°C  
Steam Cleaning upto +130°C ( for Max 30 Minutes)



**EVA PROFILE HOSE**  
**INDUSTRIAL VACUUM CLEANER HOSE**  
**SWIMMING POOL HOSE**  
**VSM - A - Surface resistance**  
**as per DIN 53482  $\leq 10^{10}$  Ohm**  
Temp. -50°C up to +60°C



**EVA PROFILE HOSE**  
**INDUSTRIAL VACUUM CLEANER HOSE**  
**SWIMMING POOL HOSE**  
**VSM - E**  
**Surface resistance  $\leq 10^6$  Ohm**  
Temp. -50°C up to +60°C



**NYLON (POLYAMIDE)**  
**CONDUIT PIPES**  
**AND GLANDS**  
Temp.: -10°C to +90°C



M.S. HOSE CLAMP



S.S. HOSE CLAMP



S.S. / M.S BOLT HEAVY TYPE  
& O.H.T.C. HOSE CLAMP



S.S. BRIDGE CLAMP



Screw cuff

Black screw cuff with a standard thread in different diameters. Other colours on request.



Standard crip cuff

Black screw cuff with different threads and out of various materials. Other colours on request.



Coupling

Screw cuff for different hoses and diameters.



Reducer

For connecting light and middle weight



Hose Connector

**Marketing**  
Ketan Patel - 91-99784 42215  
**Technical**  
Chirag Shah - 91-79903 36570  
**Director**  
S.D.Shah - 91-90990 16044



+91-79 - 22 14 0461  
+91-79 - 22 16 1360



flexaflexhoses@gmail.com



www.flexaflexhoses.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate,  
Ahmedabad - 380 002