

HOSES FOR FLOOR CARE, DUST COLLECTION & POWDER CONVEYING



EVA PROFILE HOSE
INDUSTRIAL VACUUM
CLEANER HOSE
SWIMMING POOL HOSE

Temp. -50°C up to +60°C



VAT-ELASTIC HOSE
VACUUM CLEANER HOSE

WET AND DRY FLOOR CARE

Wall Thick. 0.5 mm

Temp. 0°C up to +85°C



PVC SUCTION & DELIVERY
FOOD GRADE HOSE -FLEXANT
FOOD GRADE / PHTHALATE FREE /
ANTISTATIC

Wall Thick. 3 to 6.5 mm

Temp. 0°C up to +60°C




PU HOSE WITH RIGID HELIX
Serie 3PUR S - AL

FOOD GRADE

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C

POWDER CONVEYING



PU HOSE WITH RIGID HELIX
Serie 3PUR M - AL - ANT

FOOD GRADE / ANTISTATIC

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C

POWDER CONVEYING



PVC FLEXIBLE DUCT HOSE

GREY

Temp. 60°C



PVC FLEXIBLE DUCT HOSE

TRANSPARENT

Temp. 60°C



PU HOSE - LIGHT DUTY

Ether Grade

Wall Thick.
0.4 mm

Temp. -40°C to +100°C
 (Short-term: +125°C)



PU HOSE - HEAVY DUTY
Ether Grade

Wall Thick.
0.6 / 0.7 / 1 / 1.2 mm

Temp. -40°C to +100°C
 (Short-term: +125°C)



PU HOSE - EXTRA HEAVY DUTY
Ether Grade

FOOD GRADE / NON TOXIC

Wall Thick. 1.4 to 2.5 mm

Temp. -40°C to +100°C
 (Short-term: +125°C)



PU HOSE - SUPER HEAVY DUTY - Ether Grade

Wall Thick . 4 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



FLEXADUX HT PU POLYURETHANE HOSE FOR HIGH TEMPERATURE APPLICATIONS

Wall Thick . 0.7/1/1.4 mm

Temp. -40°C to +145°C
(Short-term: +165°C)



PU HOSE - PERMANENTLY ANTISTATIC AND FLAME RETARDANT

Wall Thick. 0.4/0.6/0.7/1/1.4/2mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PVC STEEL WIRE HOSE THUNDER HOSE

FOOD GRADE PHTHALATE FREE

Wall Thick. 3.5 to 7 mm

Temp. 70°C



PVC SEMI RIGID DUCT HOSE

Colour: Grey / Black
Range : 51 to 200 mm ID
Temp. -10°C to 70°C



HDPE SEMI RIGID SELF SUPPORTING HOSE CONDUCTIVE HOSE (EL)

Range : 51 to 160 mm ID

Temp. -20°C to 70°C



HIGH PRESSURE SUCTION AND DELIVERY HOSE

Temp. 65°C



PVC BRAIDED HOSES TRANSPARENT (HEAVY DUTY)

Wall Thick. 2.5 to 8 mm
Range : 6 mm to 76 mm
W. P. 6kg/cm² to 25kg/cm²
Temp. 70°C



SILICON DOUBLE LAYER HOSE

Wall Thick. 0.5 / 0.6 / 1 mm
Temp. -70°C to +270°C
(Short time 300°C)



THERMOPLASTIC (TPR) RUBBER HOSE

Temp. -40°C to +135°C
(short term up to +150°C)



HIGH TEMPERATURE CLIP SILICON

Range : 50 to 508 mm
Wall Thick. 0.4 mm
Temp. -60 to +300°C



NYLON (POLYAMIDE) CONDUIT PIPES AND GLANDS

Temp. : -10°C to +90°C



**PNEUMATIC TUBE
(PU TUBE)**

W.P. 6 to 10 kg/cm²



**HIGH PRESSURE AIR
CLEANING HOSES**

Range :8.5 mm to 20 mm

W.P. 30 to 60 kg/cm²

B.P. 120 to 225 kg/cm²



M.S. HOSE CLAMP



S.S. HOSE CLAMP



**S.S. / M.S BOLT HEAVY TYPE
& O.H.T.C. HOSE CLAMP**



S.S. BRIDGE CLAMP



Coupling

Screw cuff for different hoses
and diameters.



Screw cuff

Black screw cuff with a standard thread
in different diameters. Other colours on
request.



Standard crip cuff

Black screw cuff with different threads
and out of various materials. Other
colours on request.



Reducer

For connecting light and middle weight



Hose Connector

Marketing

Ketan Patel - 91-99784 42215

Technical

Chirag Shah - 91-79903 36570

Director

S.D.Shah - 91-90990 16044



+91-79 - 22 14 0461

+91-79 - 22 16 1360



flexaflexhoses@gmail.com



www.flexaflexhoses.com

FLEXAFLEX HOSES INTERNATIONAL

106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkva Gate,
Ahmedabad - 380 002