

### HOSES FOR FUME / FLUE GAS COLLECTION



**PU HOSE - LIGHT DUTY  
Ether Grade**

**Wall Thick.  
0.4 mm**

**Temp. -40°C to +100°C  
(Short-term: +125°C)**



**PU HOSE HEAVY DUTY  
Ether Grade**

**Wall Thick.  
0.6 & 0.7 mm**

**Temp. -40°C to +100°C  
(Short-term: +125°C)**



**PU HOSE - PERMANENTLY  
ANTISTATIC AND FLAME  
RETARDANT**

**Wall Thick.  
0.4/0.6/0.7/1/1.4/2mm**

**Temp. -40°C to +100°C  
(Short-term: +125°C)**



**FLEXADUX HT PU  
POLYURETHANE HOSE FOR HIGH  
TEMPERATURE APPLICATIONS**

**Wall Thick . 0.7/1/1.4 mm**

**Temp. -40°C to +145°C  
(Short-term: +165°C)**



**SILICON DOUBLE  
LAYER HOSE**


**Wall Thick. 0.5 / 0.6 / 1 mm**

**Temp. -70°C to +270°C  
(Short term: +300°C)**



**THERMOPLASTIC (TPR)  
RUBBER HOSE**

**Temp. -40°C to +135°C  
(short term up to +150°C)**



**POLYESTER FABRIC HOSE  
PVC COATED - UV RESISTANT  
BLUE - HEAVY**

**Colour: Blue / Black / Grey / Yellow  
Range: 38 mm to 1000 mm**

**Wall Thick.: 0.4 mm**

**Temp. -20°C to 70°C**



**POLYESTER FABRIC HOSE  
PVC COATED  
UV RESISTANT  
GREY - LIGHT**

**Range: 50 mm to 600 mm**

**Wall Thick.: 0.25 / 0.3**

**Temp. -20°C to 70°C**



**POLYESTER FABRIC HOSE  
PVC COATED  
FIRE RETARDANT  
BLACK**

**Range: 50 mm to 600 mm**

**Wall Thick.: 0.25 / 0.3**

**Temp. -20°C to 70°C**



**PVC FLEXIBLE DUCT HOSE  
GREY**

**Temp. 60°C**



**HIGH TEMPERATURE  
CLIP SILICON**

Range: 50 mm to 508 mm

Wall Thick.: 0.4 mm

Temp. -60°C to 300°C



**HIGH TEMPERATURE  
CLIP PTFE**

Range: 50 mm to 508 mm

Wall Thick.: 0.12 mm

Temp. -150°C to 250°C



**HIGH TEMPERATURE  
CLIP HOSES  
450 / 650 / 1100**

Range: 50 mm to 508 mm

Wall Thick.: 0.75 mm

Temp. 450°C to 1100°C



**PTFE HOSE WITH  
S. S. BRAIDING**

Convolutated PTFE  
Single Braided SS 304

SAE J517-100R14

Temp. - 60°C to + 260° C



**PTFE HOSE WITH  
S. S. BRAIDING**

Smooth Bore PTFE Single / Double  
Braided SS 303 /304

SAE J517-100R14

Temp. - 60°C to + 260° C



**FLEXIBLE METAL HOSES  
S.S. CORRUGATED  
FLEXIBLE HOSES**

Stainless steel  
AISI 304, AISI 321 and AISI316L

Temp. -270°C to +600°C

EN ISO 10380

END Connection  
as per customer specifications



**ALUMINIUM FOIL HOSE  
LIGHT / HEAVY Types**

Temp. 100°C & 250°C



**ALUMINIUM FOIL HOSE  
WITH INSULATION**

Temp. 150°C



**ALUMINIUM COMBI HOSE  
SEMI INSULATED ALUMINIUM  
FOIL HOSE**

Temp.150°C



**PP AIR HOSE**

Range: 25 to 250 mm

Temp. -20°C to +80°C



**EVA PROFILE HOSE  
INDUSTRIAL VACUUM  
CLEANER HOSE  
SWIMMING POOL HOSE**

Temp. -50°C up to +60°C



**VAT-ELASTIC HOSE  
VACUUM CLEANER HOSE**

WET AND DRY FLOOR CARE

Wall Thick. 0.5 mm

Temp. 0°C up to +85°C



**PVC BRAIDED HOSES  
TRANSPARENT (HEAVY DUTY)**

Wall Thick. 2.5 to 8 mm  
Range : 6 mm to 76 mm  
W. P. 6kg/cm<sup>2</sup> to 25kg/cm<sup>2</sup>  
Temp. 70° C



**NYLON (POLYAMIDE) CONDUIT  
PIPES AND GLANDS**

Temp. : -10°C to +90°C



**PNEUMATIC TUBE  
(PU TUBE)**

W.P. 6 to 10 kg/cm<sup>2</sup>



**HIGH PRESSURE AIR  
CLEANING HOSES**

Range :8.5 mm to 20 mm  
W.P. 30 to 60 kg/cm<sup>2</sup>  
B.P. 120 to 225 kg/cm<sup>2</sup>



M.S. HOSE CLAMP



S.S. HOSE CLAMP



S.S. / M.S BOLT HEAVY TYPE  
& O.H.T.C. HOSE CLAMP



S.S. BRIDGE CLAMP



**Coupling**

Screw cuff for different hoses  
and diameters.



**Screw cuff**

Black screw cuff with a standard thread  
in different diameters. Other colours on  
request.



**Standard crip cuff**



**Reducer**

For connecting light and middle weight



**Hose Connector**

**Marketing**  
Ketan Patel - 91-99784 42215  
**Technical**  
Chirag Shah - 91-79903 36570  
**Director**  
S.D.Shah - 91-90990 16044



+91-79 - 22 14 0461  
+91-79 - 22 16 1360



flexaflexhoses@gmail.com



www.flexaflexhoses.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkva Gate,  
Ahmedabad - 380 002