

GERMAN HOSES FOR HEATING / VENTILATION AND AIR CONDITIONING



**POLYESTER FABRIC HOSE
PVC COATED
FIRE RETARDANT
BLACK**
Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - UV RESISTANT
Heavy Duty - Flame Retardant**
Range: 38 mm to 1000 mm
Wall Thick.: 0.5 mm
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - UV RESISTANT
Heavy Duty
Antistatic and Flame Retardant**
Range: 38 mm to 1000 mm
Wall Thick.: 0.5 mm
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED
Flame Retardant /
Outer Wearstrip Profile**
Range: 150 mm to 3500 mm
Temp. -20°C to 80°C



**POLYESTER FABRIC HOSE
PVC COATED
UV RESISTANT
GREY - LIGHT**
Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - UV RESISTANT
BLUE - HEAVY**
Colour: Blue / Black / Grey / Yellow
Range: 38 mm to 1000 mm
Wall Thick.: 0.4 mm
Temp. -20°C to 70°C



**SILICON DOUBLE
LAYER HOSE**
Wall Thick.
0.5 / 0.6 / 1 mm
Temp. -70°C to +270°C
(Short time 300°C)



**PU HOSE - LIGHT DUTY
Ether Grade**
Wall Thick.
0.4 mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**PU HOSE - HEAVY DUTY
Ether Grade**
Wall Thick.
0.6 / 0.7 / 1 / 1.2 mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**FLEXADUX HT PU
POLYURETHANE HOSE FOR HIGH
TEMPERATURE APPLICATIONS**
Wall Thick. 0.7/1/1.4 mm
Temp. -40°C to +145°C
(Short-term: +165°C)



**PU HOSE - PERMANENTLY
ANTISTATIC AND FLAME
RETARDANT**

Wall Thick.
0.4/0.6/0.7/1/1.4/2mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**PVC FLEXIBLE DUCT HOSE
GREY
Temp. 60°C**



**THERMOPLASTIC (TPR)
RUBBER HOSE**

Temp. -40°C to +135°C
(short term up to +150°C)



PP AIR HOSE
Range: 25 mm to 250 mm
Temp. -20°C to +80°C



**ALUMINIUM FOIL HOSE
LIGHT / HEAVY Types**

Temp. 100°C & 250°C



**ALUMINIUM FOIL HOSE
WITH INSULATION**

Temp. 150°C



**SEMI INSULATED ALUMINIUM
FOIL HOSE**

Temp. 150°C



**ALUMINIUM SEMI-RIGID
AIR DUCT**

Temp. 150°C



**PVC SEMI RIGID DUCT
HOSE**

Colour: Grey / Black
Range : 51 to 200 mm ID
Temp. -10°C to 70°C



**HDPE SEMI RIGID SELF
SUPPORTING HOSE
CONDUCTIVE HOSE (EL)**

Range : 51 to 160 mm ID
Temp. -20°C to 70°C



**EVA PROFILE HOSE
INDUSTRIAL VACUUM
CLEANER HOSE
SWIMMING POOL HOSE**

Temp. -50°C up to +60°C



**VAT-ELASTIC HOSE
VACUUM CLEANER HOSE
WET AND DRY FLOOR CARE**

Wall Thick. 0.5 mm
Temp. 0°C up to +85°C



**NYLON (POLYAMIDE) CONDUIT
PIPES AND GLANDS**

Temp. : -10°C to +90°C



**FLEXIBLE METAL HOSES
S.S. CORRUGATED
FLEXIBLE HOSES**

Stainless steel
AISI 304, AISI 321 and AISI316L

Temp. -270°C to +600°C
EN ISO 10380

END Connection
as per customer specifications



**PVC BRAIDED HOSES
TRANSPARENT (HEAVY DUTY)**

Wall Thick. 2.5 to 8 mm
Range : 6 mm to 76 mm
W. P. 6kg/cm² to 25kg/cm²
Temp. 70° C



**PNEUMATIC TUBE
(PU TUBE)**

W.P. 6 to 10 kg/cm²



**PVC SUCTION & DELIVERY HOSE
GREEN - MEDIUM DUTY**

Range : 20 mm to 100 mm
W. P. 3.5kg/cm² to 7kg/cm²
B. P. 11kg/cm² to 24kg/cm²
Temp. 60°C



**HIGH PRESSURE AIR
CLEANING HOSES**

Range :8.5 mm to 20 mm
W.P. 30 to 60 kg/cm²
B.P. 120 to 225 kg/cm²



**THERMOPLASTIC RUBBER HOSE
AIR / PNEUMATIC**

Range :6 mm to 50 mm
W.P. 14 to 22 kg/cm²



**THERMOPLASTIC RUBBER HOSE
WATER - HOSE**

Range :12.5 / 20 / 25 mm
W.P. 10 kg/cm²



M.S. HOSE CLAMP



S.S. HOSE CLAMP



S.S. / M.S BOLT HEAVY TYPE
& O.H.T.C. HOSE CLAMP



S.S. BRIDGE CLAMP



Coupling

Screw cuff for different hoses
and diameters.



Screw cuff

Black screw cuff with a standard thread
in different diameters. Other colours on
request.



Standard crip cuff

Black screw cuff with different threads
and out of various materials. Other
colours on request.



Reducer

For connecting light and middle weight



Hose Connector

Marketing
Ketan Patel - 91-99784 42215
Technical
Chirag Shah - 91-79903 36570
Director
S.D.Shah - 91-90990 16044



+91-79 - 22 14 0461
+91-79 - 22 16 1360



flexaflexhoses@gmail.com



www.flexaflexhoses.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkva Gate,
Ahmedabad - 380 002