

### GERMAN HOSES FOR AUTO LOADERS & DRYERS / VACUUM / PNEUMATIC CONVEYING AND SILO SUCTION



**PU HOSE - HEAVY DUTY  
Ether Grade  
FOOD GRADE**  
Wall Thick.  
0.6/ 0.8/1/1.2/1.5 mm  
Temp. -40°C to +100°C  
(Short-term: +125°C)




**PU HOSE - HEAVY DUTY  
Ether Grade  
NON TOXIC**  
Wall Thick.  
0.7/ 1 / 1.4 mm  
Temp. -40°C to +100°C  
(Short-term: +125°C)



**PU HOSE - EXTRA HEAVY DUTY  
Ether Grade  
FOOD GRADE / NON TOXIC**  
Wall Thick. 2.5 mm  
Temp. -40°C to +100°C  
(Short-term: +125°C)



**PU HOSE - PERMANENTLY  
ANTISTATIC AND FLAME  
RETARDANT**  
Wall Thick.  
0.4/0.6/0.7/1/1.4/2mm  
Temp. -40°C to +100°C  
(Short-term: +125°C)



**PU HOSE FDA APPROVED  
FLEXADUX P7 L & M PU PAS FOOD  
FOOD GRADE - FDA APPROVED  
PERMANENTLY ANTISTATIC  
WITH SS 304 WIRE**  
Wall Thick . 0.7/ 1.4 mm  
Temp. -40°C to +100°C  
(Short-term: +125°C)



**FLEXADUX HT PU  
POLYURETHANE HOSE FOR HIGH  
TEMPERATURE APPLICATIONS**  
Wall Thick . 0.7/1/1.4 mm  
Temp. -40°C to +145°C  
(Short-term: +165°C)



**PU HOSE FOOD GRADE  
FLEXADUX P7 OL PU FOOD  
FOR FATTY FOOD**  
Wall Thick. 0.7 / 1.4 mm  
Temp. -40°C to +100°C  
(Short-term: +125°C)



**PU HOSE - SUPER HEAVY DUTY  
ETHER GRADE  
FOOD GRADE**  
Wall Thick . 4 mm  
Temp. -40°C to +100°C  
(Short-term: +125°C)



**PVC STEEL WIRE HOSE  
THUNDER HOSE  
FOOD GRADE  
PHTHALATE FREE**  
Wall Thick. 3.5 to 7 mm  
Temp. 70°C



**PVC SUCTION & DELIVERY  
FOOD GRADE HOSE -FLEXANT  
FOOD GRADE / PHTHALATE FREE /  
ANTISTATIC**  
Wall Thick . 3 to 6.5 mm  
Temp. 0°C up to +60°C



**PVC STEEL WIRE HOSE WITH FABRIC REINFORCEMENT**

**FOOD GRADE**

**Temp. 65°C**



**HIGH PRESSURE SUCTION AND DELIVERY HOSE**

**Temp. 65°C**



**THERMOPLASTIC RUBBER HOSE TPR HOSE**

**Wall Thick. 0.65 mm**

**Temp. -40°C to +135°C (Short time 150°C)**



**SILICON SUCTION HOSE SUPER HEAVY - FDA GRADE**

**Wall Thick. 3 mm**

**Temp. -60°C to +200°C**

**HOT PET CONVEYING**



**SILICON DOUBLE LAYER HOSE**

**Wall Thick. 1 mm**

**Temp. -70°C to +270°C (Short time 300°C)**

**HOT PET CONVEYANCE**



**SILICON DOUBLE LAYER HOSE**

**Wall Thick. 0.5 & 0.6**

**Temp. -70°C to +270°C (Short time 300°C)**



**HIGH TEMPERATURE CLIP HYPALON**

**Wall Thick. 0.4 mm**

**Temp. -40°C to 175°C**



**HIGH TEMPERATURE CLIP SILICON**

**Wall Thick. 0.4 mm**

**Temp. -60°C to 300°C**



**PU HOSE WITH RIGID HELIX Serie 3PUR S - AL**

**FOOD GRADE**

**Wall Thick. 0.75 to 1mm**

**Temp. -30°C to +80°C**

**POWDER CONVEYING**



**PU HOSE WITH RIGID HELIX Serie 3PUR M - AL - ANT**

**FOOD GRADE / ANTISTATIC**

**Wall Thick. 0.75 to 1mm**

**Temp. -30°C to +80°C**

**POWDER CONVEYING**



**FLEXIBLE METAL HOSES S.S. CORRUGATED FLEXIBLE HOSES**

**Stainless steel AISI 304, AISI 321 and AISI316L**

**Temp. -270°C to +600°C**

**EN ISO 10380**

**END Connection as per customer specifications**



**HEAVY DUTY SUCTION HOSE (PU LINED) ABRASION RESISTANT PVC HOSES**

**W. P. 2.5kg/cm<sup>2</sup> to 8kg/cm<sup>2</sup>**

**B. P. 6kg/cm<sup>2</sup> to 25kg/cm<sup>2</sup>**

**Temp. 60°C**



**PVC NON TOXIC SUCTION HOSE  
WITH ANT COPPER WIRE**  
**FOOD GRADE**  
W. P. 3.5kg/cm<sup>2</sup> to 7kg/cm<sup>2</sup>  
B. P. 11kg/cm<sup>2</sup> to 23kg/cm<sup>2</sup>  
Temp. 60°C



**PVC SUCTION & DELIVERY HOSE  
HEAVY DUTY GREY**  
Range : 25 mm to 300 mm  
W. P. 2.5kg/cm<sup>2</sup> to 8kg/cm<sup>2</sup>  
B. P. 6kg/cm<sup>2</sup> to 25kg/cm<sup>2</sup>  
Temp. 60°C



**PVC SUCTION & DELIVERY HOSE  
GREEN - MEDIUM DUTY**  
Range : 20 mm to 100 mm  
W. P. 3.5kg/cm<sup>2</sup> to 7kg/cm<sup>2</sup>  
B. P. 11kg/cm<sup>2</sup> to 24kg/cm<sup>2</sup>  
Temp. 60°C



**PVC BRAIDED HOSES  
TRANSPARENT (HEAVY DUTY)**  
Wall Thick. 2.5 to 8 mm  
Range : 6 mm to 76 mm  
W. P. 6kg/cm<sup>2</sup> to 25kg/cm<sup>2</sup>  
Temp. 70°C



**EVA PROFILE HOSE  
INDUSTRIAL VACUUM  
CLEANER HOSE  
SWIMMING POOL HOSE**  
Temp. -50°C to +60°C



**VAT-ELASTIC HOSE  
VACUUM CLEANER HOSE**  
WET AND DRY FLOOR CARE  
Wall Thick. 0.5 mm  
Temp. 0°C to +85°C



**PVC FLEXIBLE DUCT HOSE  
TRANSPARENT**  
Temp. 60°C



**PVC FLEXIBLE DUCT HOSE  
GREY**  
Temp. 60°C




**PU HOSE  
ELECTRICALLY CONDUCTIVE  
FLEXADUX P7 M PU EL**  
Wall Thick. 1.4 mm  
Temp. -40°C to 100°C



**NYLON (POLYAMIDE) CONDUIT  
PIPES AND GLANDS**  
Temp. : -10°C to +90°C



**AIR AND WATER HOSE**  
Range : 12.5 mm to 100 mm ID  
W.P. 12 kg/cm<sup>2</sup>  
Temp. -30°C to +82°C  
I.S. 446 Type - I / I.S. 444 Type - II



**PNEUMATIC TOOL HOSE**  
Range : 6.3 mm to 50 mm ID  
W.P. 14 kg/cm<sup>2</sup>  
Temp. -30°C to +82°C  
I.S. 446 : 1980 Type II



**HYDRAULIC HOSES  
SAE R1 AT**  
Range :6.3 mm to 50.8 mm  
W.P. 40 to 230 kg/cm<sup>2</sup>  
B.P. 163 to 920 kg/cm<sup>2</sup>  
Temp. -40°C to +100°C



**HYDRAULIC HOSES  
SAE R2 AT**  
Range :6.3 mm to 50.8 mm  
W.P. 82 to 400 kg/cm<sup>2</sup>  
B.P. 325 to 1630 kg/cm<sup>2</sup>  
Temp. -40°C to +100°C



**THERMOPLASTIC RUBBER HOSE  
AIR / PNEUMATIC**  
Range :6 mm to 50 mm  
W.P. 14 to 22 kg/cm<sup>2</sup>



**THERMOPLASTIC RUBBER HOSE  
WATER - HOSE**  
Range :12.5 / 20 / 25 mm  
W.P. 10 kg/cm<sup>2</sup>



**PNEUMATIC TUBE  
(PU TUBE)**  
W.P. 6 to 10 kg/cm<sup>2</sup>



**HIGH PRESSURE AIR  
CLEANING HOSES**  
Range :8.5 mm to 20 mm  
W.P. 30 to 60 kg/cm<sup>2</sup>  
B.P. 120 to 225 kg/cm<sup>2</sup>



M.S. HOSE CLAMP



S.S. HOSE CLAMP



S.S. / M.S BOLT HEAVY TYPE  
& O.H.T.C. HOSE CLAMP



S.S. BRIDGE CLAMP



**Coupling**  
Screw cuff for different hoses  
and diameters.



**Screw cuff**  
Black screw cuff with a standard thread  
in different diameters. Other colours on  
request.



**Standard crip cuff**  
Black screw cuff with different threads  
and out of various materials. Other  
colours on request.



**Reducer**  
For connecting light and middle weight



**Hose Connector**

**Marketing**  
Ketan Patel - 91-99784 42215  
**Technical**  
Chirag Shah - 91-79903 36570  
**Director**  
S.D.Shah - 91-90990 16044



+91-79 - 22 14 0461  
+91-79 - 22 16 1360



flexaflexhoses@gmail.com



www.flexaflexhoses.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkua Gate,  
Ahmedabad - 380 002