

GERMAN HOSES FOR PRINTING / LAMINATION / COATING AND LASER / PLASMA CUTTING INDUSTRIES



SILICON DOUBLE LAYER HOSE

Wall Thick. 0.5 / 0.6 / 1 mm

Temp. -70°C to +270°C
(Short time 300°C)



THERMOPLASTIC (TPR) RUBBER HOSE

Temp. -40°C to +135°C
(short term up to +150°C)



PU HOSE - LIGHT DUTY Ether Grade

Wall Thick.
0.4 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PU HOSE EXTRA HEAVY DUTY Ether Grade

Wall Thick.
1.2 / 1.4 / 1.5 / 2.5 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



FLEXADUX HT PU POLYURETHANE HOSE FOR HIGH TEMPERATURE APPLICATIONS

Wall Thick . 0.7/1/1.4 mm

Temp. -40°C to +145°C
(Short-term: +165°C)



PVC STEEL WIRE HOSE THUNDER HOSE

FOOD GRADE
PHTHALATE FREE

Wall Thick. 3.5 to 7 mm

Temp. 70°C



PVC SUCTION & DELIVERY FOOD GRADE HOSE -FLEXANT FOOD GRADE / PHTHALATE FREE / ANTISTATIC

Wall Thick . 3 to 6.5 mm

Temp. 0°C to +60°C




HIGH PRESSURE SUCTION AND DELIVERY HOSE

Temp. 65°C



PVC FLEXIBLE DUCT HOSE GREY

Temp. 60°C



POLYESTER FABRIC HOSE PVC COATED - UV RESISTANT BLUE - HEAVY

Colour: Blue / Black / Grey / Yellow

Range: 38 mm to 1000 mm

Wall Thick.: 0.4 mm

Temp. -20°C to 70°C



POLYESTER FABRIC HOSE
PVC COATED
UV RESISTANT
GREY - LIGHT
 Range: 50 mm to 600 mm
 Wall Thick.: 0.25 / 0.3
 Temp. -20°C to 70°C



POLYESTER FABRIC HOSE
PVC COATED
FIRE RETARDANT
BLACK
 Range: 50 mm to 600 mm
 Wall Thick.: 0.25 / 0.3
 Temp. -20°C to 70°C



ALUMINIUM FOIL HOSE
LIGHT / HEAVY Types
 Temp. 100°C & 250°C



ALUMINIUM FOIL HOSE
WITH INSULATION
 Temp. 150°C



ALUMINIUM COMBI HOSE
SEMI INSULATED ALUMINIUM
FOIL HOSE
 Temp. 150°C



PP AIR HOSE
 Range: 25 to 250 mm
 Temp. -20°C to +80°C



FLEXIBLE METAL HOSES
S.S. CORRUGATED
FLEXIBLE HOSES
 Stainless steel
 AISI 304, AISI 321 and AISI316L
 Temp. -270°C to +600°C
 EN ISO 10380

END Connection
 as per customer specifications



PTFE HOSE WITH
S. S. BRAIDING
 Convoluted PTFE
 Single Braided SS 304
 SAE J517-100R14
 Temp. - 60°C to + 260° C



PTFE HOSE WITH
S. S. BRAIDING
 Smooth Bore PTFE Single / Double
 Braided SS 303 /304
 SAE J517-100R14
 Temp. - 60°C to + 260° C



FDA-GRADE CHEMICAL
HOSE
UHMWPE
 Range : 19 mm to 102 mm ID
 W.P. 16 kg/cm²
 Temp. -25°C to 100°C
 Steam Cleaning upto +130°C (for Max 30 Minutes)



XLPE CHEMICAL HOSE
SOLVENT HANDLING HOSE
 Range : 25 mm to 50 mm ID
 W.P. 14 kg/cm²
 Temp. -30°C to 90°C
 Steam Cleaning upto +130°C (for Max 30 Minutes)



SUPER STEAM HOSE
DOUBLE WIRE BRAIDED
 Range :12.7 mm to 50 mm
 W.P. 17 kg/cm²
 B.P. 170 kg/cm²
 Temp. -40°C to +232°C
 IS : 10655 Type 3 & B.S. : 5342 Type 2



EPDM CHEMICAL HOSE

Range :19 mm to 50 mm
W.P. 12 kg/cm²
B.P. 48 kg/cm²
Temp. -30°C to +100°C



HYDRAULIC HOSES

SAE R1 AT

Range :6.3 mm to 50.8 mm
W.P. 40 to 230 kg/cm²
B.P. 163 to 920 kg/cm²
Temp. -40°C to +100°C



HYDRAULIC HOSES

SAE R2 AT

Range :6.3 mm to 50.8 mm
W.P. 82 to 400 kg/cm²
B.P. 325 to 1630 kg/cm²
Temp. -40°C to +100°C



EVA PROFILE HOSE

INDUSTRIAL VACUUM CLEANER HOSE SWIMMING POOL HOSE

Temp. -50°C to +60°C



VAT-ELASTIC HOSE

VACUUM CLEANER HOSE

WET AND DRY FLOOR CARE
Wall Thick. 0.5 mm
Temp. 0°C to +85°C



NYLON (POLYAMIDE) CONDUIT PIPES AND GLANDS

Temp. : -10°C to +90°C



PVC BRAIDED HOSES

TRANSPARENT (HEAVY DUTY)

Wall Thick. 2.5 to 8 mm
Range : 6 mm to 76 mm
W. P. 6kg/cm² to 25kg/cm²
Temp. 70°C



PVC SUCTION & DELIVERY HOSE

GREEN - MEDIUM DUTY

Range : 20 mm to 100 mm
W. P. 3.5kg/cm² to 7kg/cm²
B. P. 11kg/cm² to 24kg/cm²
Temp. 60°C



THERMOPLASTIC RUBBER HOSE

AIR / PNEUMATIC

Range :6 mm to 50 mm
W.P. 14 to 22 kg/cm²



THERMOPLASTIC RUBBER HOSE

WATER - HOSE

Range :12.5 / 20 / 25 mm
W.P. 10 kg/cm²



PNEUMATIC TUBE

(PU TUBE)

W.P. 6 to 10 kg/cm²



HIGH PRESSURE AIR CLEANING HOSES

Range :8.5 mm to 20 mm
W.P. 30 to 60 kg/cm²
B.P. 120 to 225 kg/cm²



M.S. HOSE CLAMP



S.S. HOSE CLAMP



**S.S. / M.S BOLT HEAVY TYPE
& O.H.T.C. HOSE CLAMP**



S.S. BRIDGE CLAMP



Coupling
Screw cuff for different hoses
and diameters.



Screw cuff
Black screw cuff with a standard thread
in different diameters. Other colours on
request.



Standard crip cuff
Black screw cuff with different threads
and out of various materials. Other
colours on request.



Reducer
For connecting light and middle weight



Hose Connector

Marketing

Ketan Patel - 91-99784 42215

Technical

Chirag Shah - 91-79903 36570

Director

S.D.Shah - 91-90990 16044



+91-79 - 22 14 0461

+91-79 - 22 16 1360



flexaflexhoses@gmail.com



www.flexaflexhoses.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkva Gate,
Ahmedabad - 380 002