

German Hoses for Spinning / Weaving / Processing / Printing / Hosiery



PVC FLEXIBLE DUCT HOSE
Grey

Temp. 60°C



PVC FLEXIBLE DUCT HOSE
Transparent

Temp. 60°C



PVC FLEXIBLE DUCT HOSE
Blue

Temp. 60°C



PU HOSE - LIGHT DUTY
Ether Grade

Wall Thick.
0.4 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PU HOSE - HEAVY DUTY
Ether Grade

Wall Thick.
0.6 / 0.7 / 1 / mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PU HOSE
EXTRA HEAVY DUTY
Ether Grade

Wall Thick.
1.2 mm to 2.5 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



**PU HOSE - PERMANENTLY
ANTISTATIC AND FLAME
RETARDANT**

Wall Thick.
0.4/0.6/0.7/1/1.4/2mm

Temp. -40°C to +100°C
(Short-term: +125°C)



**FLEXADUX HT PU
POLYURETHANE HOSE FOR HIGH
TEMPERATURE APPLICATIONS**

Wall Thick . 0.7/1/1.4 mm

Temp. -40°C to +145°C
(Short-term: +165°C)



PU HOSE WITH RIGID HELIX
Serie 3PUR S - AL

FOOD GRADE

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C

POWDER CONVEYING



PU HOSE WITH RIGID HELIX
Serie 3PUR M - AL - ANT

FOOD GRADE / ANTISTATIC

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C

POWDER CONVEYING



PP AIR HOSE

Range: 25 to 250 mm

Temp. -20°C to +80°C



PVC STEEL WIRE HOSE THUNDER HOSE

FOOD GRADE
PHTHALATE FREE

Wall Thick. 3.5 to 7 mm

Temp. 70°C



SILICON DOUBLE LAYER HOSE

Wall Thick. 0.5 / 0.6 / 1 mm

Temp. -70°C to +270°C
(Short time 300°C)



THERMOPLASTIC (TPR) RUBBER HOSE

Temp. -40°C to +135°C
(short term up to +150°C)



POLYESTER FABRIC HOSE PVC COATED UV RESISTANT GREY - LIGHT

Range: 50 mm to 600 mm

Wall Thick.: 0.25 / 0.3

Temp. -20°C to 70°C



POLYESTER FABRIC HOSE PVC COATED - UV RESISTANT BLUE - HEAVY

Colour: Blue / Black / Grey / Yellow

Range: 38 mm to 1000 mm

Wall Thick.: 0.4 mm

Temp. -20°C to 70°C



Black Synthetic Hose - ELGI

Range: 100 / 125 mm

Length : 300 mm



Rixin Blow Hose

Range : 75 / 100 / 125 mm

Length :

1.5 / 2.5 / 2.8 / 3 mtrs



PVC BRAIDED HOSES TRANSPARENT (HEAVY DUTY)

Wall Thick. 2.5 to 8 mm

Range : 6 mm to 76 mm

W. P. 6kg/cm² to 25kg/cm²

Temp. 70° C



THERMOPLASTIC RUBBER HOSE AIR / PNEUMATIC

Range : 6 mm to 50 mm

W.P. 14 to 22 kg/cm²



PNEUMATIC TUBE (PU TUBE)

W.P. 6 to 10 kg/cm²



HIGH PRESSURE AIR CLEANING HOSES

Range : 8.5 mm to 20 mm

W.P. 30 to 60 kg/cm²

B.P. 120 to 225 kg/cm²



HYDRAULIC HOSES SAE R1 AT

Range :6.3 mm to 50.8 mm
W.P. 40 to 230 kg/cm²
B.P. 163 to 920 kg/cm²
Temp. -40°C to +100°C



HYDRAULIC HOSES SAE R2 AT

Range :6.3 mm to 50.8 mm
W.P. 82 to 400 kg/cm²
B.P. 325 to 1630 kg/cm²
Temp. -40°C to +100°C



PNEUMATIC TOOL HOSE

Range : 6.3 mm to 50 mm ID
W.P. 14 kg/cm²
Temp. -30°C to +82°C
I.S. 446 : 1980 Type II



AIR AND WATER HOSE

Range : 12.5 mm to 100 mm ID
W.P. 12 kg/cm²
Temp. -30°C to +82°C
I.S. 446 Type - I / I.S. 444 Type - II



EPDM CHEMICAL HOSE

Range :19 mm to 50 mm
W.P. 12 kg/cm²
B.P. 48 kg/cm²
Temp. -30°C to +100°C



HIGH PRESSURE SUCTION AND DELIVERY HOSE

Temp. 65°C



PVC SUCTION & DELIVERY HOSE HEAVY DUTY GREY

Range : 40 mm to 300 mm
W. P. 2.5kg/cm² to 8kg/cm²
B. P. 6kg/cm² to 25kg/cm²
Temp. 60°C



PVC SUCTION & DELIVERY HOSE GREEN - MEDIUM DUTY

Range : 200 mm to 100 mm
W. P. 3.5kg/cm² to 7kg/cm²
B. P. 11kg/cm² to 24kg/cm²
Temp. 60°C



PVC BRAIDED WATER HOSE

Green - Medium Duty
Working Pressure :
5kg/cm² to 7kg/cm²
Temp. 60°C



EVA PROFILE HOSE INDUSTRIAL VACUUM CLEANER HOSE SWIMMING POOL HOSE

Temp. -50°C up to +60°C



VAT-ELASTIC HOSE VACUUM CLEANER HOSE

WET AND DRY FLOOR CARE
Wall Thick. 0.5 mm
Temp. 0°C up to +85°C



NYLON (POLYAMIDE) CONDUIT PIPES AND GLANDS

Temp. : -10°C to +90°C



PVC Straight Hose - 2.5 meter



**Murata Autoconer Hose
125 mm - 2.5 meter**



OHTC PVC Pipe - Black



M.S. HOSE CLAMP



S.S. HOSE CLAMP



**S.S. / M.S BOLT HEAVY TYPE
& O.H.T.C. HOSE CLAMP**



S.S. BRIDGE CLAMP



Coupling

Screw cuff for different hoses
and diameters.



Screw cuff

Black screw cuff with a standard thread
in different diameters. Other colours on
request.



Standard crip cuff

Black screw cuff with different threads
and out of various materials. Other
colours on request.



Reducer

For connecting light and middle weight



Hose Connector

Marketing

Ketan Patel - 91-99784 42215

Technical

Chirag Shah - 91-79903 36570

Director

S.D.Shah - 91-90990 16044



+91-79 - 22 14 0461

+91-79 - 22 16 1360



flexaflexhoses@gmail.com



www.flexaflexhoses.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkva Gate,
Ahmedabad - 380 002