

PU HOSE WITH RIGID HELIX

Serie 3PUR M - AL - **ANT**

FOOD GRADE



Structure :

Food grade polyether polyurethane wall in accordance with the modified EU Regulation 10/2011, reinforced with shock - resistant plastic spiral. Copper wire for grounding. Smooth bore.

Characteristics :

Resistant to hydrolysis and microbes, good flexibility, smooth bore, **Food Grade**

Applications:

Light suction and transport of abrasive particles, granules, waste, dust, in wood, textile mill, pharma and plastic industry, sweepers, lawn movers.

Temperature range:

- 30 / + 80 °C

Colour:

Transparent, Grey helix



Special construction:

Also available Serie 3 PUR S AL:
food grade version



Cuffs screwable on request



int mm	kg/m	mm	mm	bar	bar	m
20	0.170	0.50	30.00	1.80	0.63	25.00
25	0.190	0.55	37.50	1.60	0.63	25.00
30	0.235	0.55	45.00	1.50	0.63	25.00
32	0.250	0.55	48.00	1.50	0.63	25.00
35	0.270	0.55	52.50	1.50	0.63	25.00
38	0.300	0.60	57.00	1.50	0.50	25.00
40	0.310	0.60	60.00	1.50	0.50	25.00
45	0.350	0.60	67.50	1.50	0.45	25.00
50	0.385	0.60	75.00	1.50	0.45	25.00
60	0.465	0.60	90.00	1.00	0.30	25.00
65	0.545	0.65	97.50	1.00	0.30	25.00
70	0.585	0.70	105.00	1.00	0.26	25.00
75	0.630	0.70	112.50	1.00	0.26	25.00
80	0.700	0.70	120.00	1.00	0.16	25.00
90	0.800	0.70	135.00	1.00	0.16	25.00
100	0.920	0.70	150.00	1.00	0.16	15.00
110	1.000	0.75	165.00	0.80	0.16	15.00
120	1.110	0.75	180.00	0.80	0.16	15.00
125	1.165	0.80	187.50	0.80	0.16	15.00
140	1.375	0.85	210.00	0.60	0.16	15.00
150	1.540	0.85	225.00	0.60	0.16	15.00
160	1.642	0.90	240.00	0.50	0.16	15.00
180	2.105	1.00	270.00	0.50	0.16	10.00
200	2.340	1.10	300.00	0.40	0.15	10.00
250	2.925	1.10	375.00	0.30	0.15	10.00

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458

Chirag Shah - Technical
+91-79903 36570

S.D. Shah - Director
+91-90990 16044

flexaflexhoses@gmail.com

www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002