

**THE ULTIMATE DESTINATION
FOR INDUSTRIAL FLEXIBLE HOSES**

www.flexaflexhoses.com

IMPORTER OF FLEXIBLE HOSES FOR

Auto loaders, Hopper dryers, Multilayer film plants, Flexographic printing machine, Rotogravure printing machine, Offset printing machine, Extrusion, Blow moulding, PVC, HDPE, CPVC, PP Pipe manufacturing, Packaging Industry, Masterbatch Industry, Speciality Compounds, Food and Pharma.



Wall Thick 2.5mm
Temp. -40°C up to +100°C

**PU HOSE - HEAVY DUTY
ETHER GRADE**



Wall Thick 1.4mm
Temp. -40°C up to +100°C

**PU HOSE - HEAVY DUTY
ETHER GRADE**



Wall Thick 3.5 to 7 mm
Temp. 70°C

**PVC STEEL WIRE HOSE
FOOD GRADE - PHTHALATE FREE**




Wall Thick: 0.5, 0.6 & 1mm
Temp. -70°C to +270°C

**SILICON DOUBLE LAYER
HOSE**



Wall Thick 0.65 mm
Temp. -40°C to +135°C

**THERMOPLASTIC RUBBER
HOSE**



Wall Thick 0.75 to 1mm
Temp. -30°C to +80°C

**PU HOSE WITH RIGID
HELIX**



Wall Thick 3 to 6.5 mm
Temp. 0°C up to +60°C

**PVC SUCTION & DELIVERY HOSE
FOOD GRADE - PHTHALATE FREE - ANT**



W.P. 3.5kg/cm² to 7kg/cm²
B.P. 11kg/cm² to 23kg/cm²
Temp. 60°C

**PVC NON TOXIC SUCTION HOSE
WITH ANT COPPER WIRE**



Temp. -270°C to +600°C
END Connection
as per customer specifications

**FLEXIBLE METAL HOSES
S.S. CORRUGATED FLEXIBLE HOSES**
Stainless steel
AISI 304, AISI 321 and AISI 316L
EN ISO 10380




Temp. -25°C to +100°C

**FDA-GRADE CHEMICAL
HOSE - UHMWPE**
W.P. 16 kg/cm² / B.P. 48 kg/cm²
Steam Cleaning up to +130°C (for Max 30Minutes)



temp. -40°C to +100°C

**HYDRAULIC HOSES
SAE R1 AT**
W.P. 40 to 230 kg/cm²
B.P. 163 to 920 kg/cm²



Wall Thick. 2.5 to 8 mm
Green
W.P. 3.5kg/cm² to 7kg/cm²
B.P. 11kg/cm² to 24kg/cm²
Temp. 60°C

**PVC SUCTION & DELIVERY HOSE
GREEN / PVC BRAIDED HOSE**



Pooja Shah : +91-7069096458

Marketing : +91-99784 42215,

Chirag Shah - Technical : + 91-79903 36570

S.D.Shah - Director : +91-90990 16044



FLEXAFLEX HOSES INTERNATIONAL
106, Kailashpati Chamber Reid Road,
O/S. Panchkuva Gate, Ahmedabad - 380002

flexaflexhoses@gmail.com

www.flexaflexhoses.com