

flexaflex

**THE ULTIMATE DESTINATION
FOR INDUSTRIAL FLEXIBLE HOSES**

**HOSES FOR FLOOR CARE,
DUST COLLECTION &
POWDER CONVEYING.**



Contact US



Pooja Shah - Sales

+91-99784 42215

+91-70690 96458



Chirag Shah - Technical

+91-79903 36570



S.D. Shah - Director

+91-90990 16044



flexaflexhoses@gmail.com



FLEXAFLEX HOSES INTERNATIONAL

106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002

OUR PROFILE

Flexaflex Hoses International are the Leading Hose Suppliers in Ahmedabad, Gujarat, India actively engaged in importing technical industrial hoses from Germany and Europe, Taiwan & China and catering pan India.



www.flexaflexhoses.com

www.hosesmarket.com





EVA PROFILE HOSE
INDUSTRIAL VACUUM
CLEANER HOSE
SWIMMING POOL HOSE

Temp. -50°C up to +60°C



VAT-ELASTIC HOSE
VACUUM CLEANER HOSE
WET AND DRY FLOOR CARE

Wall Thick. 0.5 mm

Temp. 0°C up to +85°C



PVC SUCTION & DELIVERY
FOOD GRADE HOSE -FLEXANT
FOOD GRADE / PHTHALATE FREE /
ANTISTATIC

Wall Thick. 3 to 6.5 mm

Temp. 0°C up to +60°C



PU HOSE WITH RIGID HELIX
Serie 3PUR S - AL
FOOD GRADE

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C

POWDER CONVEYING



PU HOSE WITH RIGID HELIX
Serie 3PUR M - AL - ANT
FOOD GRADE / ANTISTATIC

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C

POWDER CONVEYING



PVC FLEXIBLE DUCT HOSE
GREY

Temp. 60°C



PVC FLEXIBLE DUCT HOSE
TRANSPARENT

Temp. 60°C



PU HOSE - LIGHT DUTY
Ether Grade

Wall Thick.
0.4 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PU HOSE - HEAVY DUTY
Ether Grade

Wall Thick.
0.6 / 0.7 / 1 / 1.2 / 1.4 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PU HOSE - EXTRA HEAVY DUTY
Ether Grade

Wall Thick. 2.5 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PU HOSE - SUPER HEAVY
DUTY - Ether Grade

Wall Thick. 4 mm

Temp. -40°C to +100°C
(Short-term: +125°C)



FLEXADUX HT PU
POLYURETHANE HOSE FOR HIGH
TEMPERATURE APPLICATIONS

Wall Thick. 0.7/1/1.4 mm

Temp. -40°C to +145°C
(Short-term: +165°C)



PU HOSE - PERMANENTLY
ANTISTATIC AND FLAME
RETARDANT

Wall Thick.
0.4/0.6/0.7/1/1.4/2mm

Temp. -40°C to +100°C
(Short-term: +125°C)



PVC STEEL WIRE HOSE
THUNDER HOSE

FOOD GRADE

Wall Thick. 3.5 to 7 mm

Temp. 70°C




PVC SEMI RIGID SELF SUPPORTING HOSE

Colour: Grey

Range : 51 to 200 mm ID

Temp. -10°C to 70°C



PVC BRAIDED HOSES TRANSPARENT (HEAVY DUTY)

Wall Thick. 2.5 to 8 mm

Range : 6 mm to 76 mm

W. P. 6kg/cm² to 25kg/cm²

Temp. 70°C



SILICON DOUBLE LAYER HOSE

Wall Thick. 0.7 / 1 mm

Temp. -70°C to +270°C (Short time 300°C)



HIGH TEMPS.SILICON for Air/ Hot PET Granules

Wall Thick. 5 mm

Temp. -70°C to +200°C



THERMOPLASTIC (TPR) RUBBER HOSE

Temp. -40°C to +135°C (short term up to +150°C)



HIGH TEMPERATURE CLIP SILICON

Range : 50 to 508 mm

Wall Thick. 0.4 mm

Temp. -60 to +300°C



VACUUM LIFT HOSE BLACK - ORANGE

Range : 100, 120, 150, 160, 180, 200mm

Temp. - 85°C



POLYESTER FABRIC HOSE PVC COATED

UV / Flame Resistant - Antistatic

Grey / Blue / Yellow / White

Wall Thick. 0.35 / 0.4 / 0.5

Temp. -30°C to +70°C



PP Air Hose

Colour: Ivory

Temp: -20°C to +80°C



M.S. HOSE CLAMP



S.S. HOSE CLAMP



S.S. / M.S BOLT HEAVY TYPE & O.H.T.C. HOSE CLAMP



S.S. BRIDGE CLAMP



Coupling

Screw cuff for different hoses and diameters.



Standard crip cuff

Black screw cuff with different threads and out of various materials. Other colours on request.



Reducer

For connecting light and middle weight



Hose Connector