

The logo for flexaflex, featuring the brand name in a bold, lowercase sans-serif font. The letter 'A' is stylized with a lightning bolt symbol integrated into its center. The logo is enclosed within a thin black oval border.

THE ULTIMATE DESTINATION
FOR INDUSTRIAL FLEXIBLE HOSES

FLEXAFLEX HOSES INTERNATIONAL

HOSES FOR FUME / FLUE GAS COLLECTION



OUR PROFILE

Flexaflex Hoses International are the Leading Hose Suppliers in Ahmedabad, Gujarat, India actively engaged in importing technical industrial hoses from Germany and Europe, Taiwan & China and catering pan India.

 flexaflexhoses@gmail.com

www.flexaflexhoses.com | www.hosesmarket.com 



Pooja Shah - Sales

**+91-99784 42215
+91-70690 96458**



Chirag Shah - Technical

+91-79903 36570



S.D. Shah - Director

+91-90990 16044



FLEXAFLEX HOSES INTERNATIONAL

106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002





**PU HOSE - LIGHT DUTY
Ether Grade**

**Wall Thick.
0.4 mm**

**Temp. -40°C to +100°C
(Short-term: +125°C)**



**PU HOSE HEAVY DUTY
Ether Grade**

**Wall Thick.
0.6 & 0.7 mm**

**Temp. -40°C to +100°C
(Short-term: +125°C)**



**PU HOSE - PERMANENTLY
ANTISTATIC AND FLAME
RETARDANT**

**Wall Thick.
0.4/0.6/0.7/1/1.4/2mm**

**Temp. -40°C to +100°C
(Short-term: +125°C)**



**FLEXADUX HT PU
POLYURETHANE HOSE FOR HIGH
TEMPERATURE APPLICATIONS**

Wall Thick . 0.7/1/1.4 mm

**Temp. -40°C to +145°C
(Short-term: +165°C)**



**SILICON DOUBLE
LAYER HOSE**

Wall Thick. 0.5 / 0.6 / 1 mm

**Temp. -70°C to +270°C
(Short term: +300°C)**



**THERMOPLASTIC (TPR)
RUBBER HOSE**

**Temp. -40°C to +135°C
(short term up to +150°C)**



**POLYESTER FABRIC HOSE
PVC COATED
UV RESISTANT - FIRE RETARDANT
BLUE - HEAVY**

**Colour: Blue / Black / Grey / Yellow
Range: 38 mm to 1000 mm
Wall Thick.: 0.4 mm
Temp. -20°C to 70°C**



**POLYESTER FABRIC HOSE
PVC COATED
UV RESISTANT
GREY - LIGHT**

**Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C**



**POLYESTER FABRIC HOSE
PVC COATED
FIRE RETARDANT
BLACK**

**Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C**



**PVC FLEXIBLE DUCT HOSE
GREY**

Temp. 60°C



**HIGH TEMPERATURE
CLIP SILICON**

**Range: 50 mm to 508 mm
Wall Thick.: 0.4 mm
Temp. -60°C to 300°C**



**HIGH TEMPERATURE
CLIP PTFE**

**Range: 50 mm to 508 mm
Wall Thick.: 0.12 mm
Temp. -150°C to 250°C**




**HIGH TEMPERATURE
CLIP HOSES
450 / 650 / 1100**

**Range: 50 mm to 508 mm
Wall Thick.: 0.75 mm
Temp. 450°C to 1100°C**



**PTFE HOSE WITH
S. S. BRAIDING
Convuluted PTFE
Single Braided SS 304
SAE J517-100R14**

Temp. - 60°C to + 260°C



**PTFE HOSE WITH
S. S. BRAIDING**
Smooth Bore PTFE Single / Double
Braided SS 303 /304
SAE J517-100R14
Temp. - 60°C to + 260°C



**FLEXIBLE METAL HOSES
S.S. CORRUGATED
FLEXIBLE HOSES**
Stainless steel
AISI 304, AISI 321 and AISI316L
Temp. -270°C to +600°C
EN ISO 10380

END Connection
as per customer specifications



**ALUMINIUM FOIL HOSE
LIGHT / HEAVY Types**
Temp. 100°C & 250°C



**ALUMINIUM FOIL HOSE
WITH INSULATION**
Temp. 150°C



**ALUMINIUM COMBI HOSE
SEMI INSULATED ALUMINIUM
FOIL HOSE**
Temp. 150°C



PP AIR HOSE
Range: 25 to 250 mm
Temp. -20°C to +80°C



**EVA PROFILE HOSE
INDUSTRIAL VACUUM
CLEANER HOSE
SWIMMING POOL HOSE**
Temp. -50°C up to +60°C



**VAT-ELASTIC HOSE
VACUUM CLEANER HOSE**
WET AND DRY FLOOR CARE
Wall Thick. 0.5 mm
Temp. 0°C up to +85°C



**PVC BRAIDED HOSES
TRANSPARENT (HEAVY DUTY)**
Wall Thick. 2.5 to 8 mm
Range : 6 mm to 76 mm
W. P. 6kg/cm² to 25kg/cm²
Temp. 70°C



**PNEUMATIC TUBE
PU TUBE & FITTINGS**
W.P. 6 to 10 kg/cm²



**HIGH PRESSURE AIR
CLEANING HOSES**
Range :8.5 mm to 20 mm
W.P. 30 to 60 kg/cm²
B.P. 120 to 225 kg/cm²



M.S. HOSE CLAMP



S.S. HOSE CLAMP



Coupling
Screw cuff for different hoses
and diameters.



Standard crip cuff
Black screw cuff with different threads
and out of various materials. Other
colours on request.



Reducer
For connecting light and middle weight



Hose Connector



**S.S. / M.S BOLT HEAVY TYPE
& O.H.T.C. HOSE CLAMP**



S.S. BRIDGE CLAMP