

THE ULTIMATE DESTINATION FOR INDUSTRIAL FLEXIBLE HOSES




FLEXAFLEX HOSES INTERNATIONAL

GERMAN HOSES FOR HEATING / VENTILATION AND AIR CONDITIONING

OUR PROFILE

Flexaflex Hoses International are the Leading Hose Suppliers in Ahmedabad, Gujarat, India actively engaged in importing technical industrial hoses from Germany and Europe, Taiwan & China and catering pan India.



Contact US



Pooja Shah - Sales

+91-99784 42215

+91-70690 96458



Chirag Shah - Technical

+91-79903 36570



S.D. Shah - Director

+91-90990 16044



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL

106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002





**POLYESTER FABRIC HOSE
PVC COATED
FIRE RETARDANT
BLACK**

Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - UV RESISTANT
Heavy Duty - Fire Retardant**

Range: 38 mm to 1000 mm
Wall Thick.: 0.5 mm
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - UV RESISTANT
Heavy Duty
Antistatic and Fire Retardant**

Range: 38 mm to 1000 mm
Wall Thick.: 0.5 mm
Temp. -20°C to 70°C




**POLYESTER FABRIC HOSE
PVC COATED
Fire Retardant /
Outer Wearstrip Profile**

Range: 150 mm to 3500 mm
Temp. -20°C to 80°C



**POLYESTER FABRIC HOSE
PVC COATED
UV Resistant and Fire Retardant**

GREY - LIGHT
Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - BLUE - HEAVY**

UV Resistant and Fire Retardant
Colour: Blue / Black / Grey / Yellow
Range: 38 mm to 1000 mm
Wall Thick.: 0.4 mm
Temp. -20°C to 70°C



**SILICON DOUBLE
LAYER HOSE**

Wall Thick.
0.5 / 0.6 / 1 mm
Temp. -70°C to +270°C
(Short time 300°C)




**PU HOSE - LIGHT DUTY
Ether Grade**

Wall Thick.
0.4 mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**PU HOSE - HEAVY DUTY
Ether Grade**

Wall Thick.
0.6 / 0.7 / 1 / 1.2 mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**FLEXADUX HT PU
POLYURETHANE HOSE FOR HIGH
TEMPERATURE APPLICATIONS**

Wall Thick . 0.7/1/1.4 mm
Temp. -40°C to +145°C
(Short-term: +165°C)




**PU HOSE - PERMANENTLY
ANTISTATIC AND FLAME
RETARDANT**

Wall Thick.
0.4/0.6/0.7/1/1.4/2mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**PVC FLEXIBLE DUCT HOSE
GREY**

Temp. 60°C



**THERMOPLASTIC (TPR)
RUBBER HOSE**

Temp. -40°C to +135°C
(short term up to +150°C)



PP AIR HOSE

Range: 25 mm to 250 mm
Temp. -20°C to +80°C



**ALUMINIUM FOIL HOSE
LIGHT / HEAVY Types**

Temp. 100°C & 250°C



**ALUMINIUM FOIL HOSE
WITH INSULATION**

Temp. 150°C



SEMI INSULATED ALUMINIUM FOIL HOSE

Temp. 150°C



ALUMINIUM SEMI-RIGID AIR DUCT

Temp. 150°C




PVC SELF SUPPORTING HOSE

Colour: Grey
Range : 51 to 200 mm ID
Temp. -10°C to 70°C



**EVA PROFILE HOSE
INDUSTRIAL VACUUM
CLEANER HOSE
SWIMMING POOL HOSE**

Temp. -50°C up to +60°C



**VAT-ELASTIC HOSE
VACUUM CLEANER HOSE**

WET AND DRY FLOOR CARE
Wall Thick. 0.5 mm
Temp. 0°C up to +85°C



**NYLON (POLYAMIDE) CONDUIT
PIPES AND GLANDS**

Temp. : -10°C to +90°C



**FLEXIBLE METAL HOSES
S.S. CORRUGATED
FLEXIBLE HOSES**

Stainless steel
AISI 304, AISI 321 and AISI316L
Temp. -270°C to +600°C
EN ISO 10380



**PVC BRAIDED HOSES
TRANSPARENT (HEAVY DUTY)**

Wall Thick. 2.5 to 8 mm
Range : 6 mm to 76 mm
W. P. 6kg/cm² to 25kg/cm²
Temp. 70° C



**PNEUMATIC TUBE
PU TUBE & FITTINGS**

W.P. 6 to 10 kg/cm²



**PVC SUCTION & DELIVERY HOSE
GREEN - MEDIUM DUTY**

Range : 20 mm to 100 mm
W. P. 3.5kg/cm² to 7kg/cm²
B. P. 11kg/cm² to 24kg/cm²
Temp. 60°C




**HIGH PRESSURE AIR
CLEANING HOSES**

Range : 8.5 mm to 20 mm
W.P. 30 to 60 kg/cm²
B.P. 120 to 225 kg/cm²



**THERMOPLASTIC RUBBER HOSE
AIR / PNEUMATIC**

Range : 6 mm to 50 mm
W.P. 14 to 22 kg/cm²



**THERMOPLASTIC RUBBER HOSE
WATER - HOSE**

Range : 12.5 / 20 / 25 mm
W.P. 10 kg/cm²



M.S. HOSE CLAMP



S.S. HOSE CLAMP



**S.S. / M.S BOLT HEAVY TYPE
& O.H.T.C. HOSE CLAMP**



S.S. BRIDGE CLAMP



Coupling
Screw cuff for different hoses and diameters.



Standard crip cuff
Black screw cuff with different threads and out of various materials. Other colours on request.



Reducer
For connecting light and middle weight



Hose Connector