

# HIGH TEMPERATURE CLIP ARAMID

Temp. - 60° C to + 260° C



## Structure:

Light weight and very flexible Silicone ducting

## Material:

One-side Silicone-coated Aramid; fabric, inside: silver / outside: green

## Properties

Good temperature resistance, outer wear strip, good resistance to mechanical influences and vibrations

## Application

Suction of hot fumes, gases or dust in all fields of industry

## Temperature Resistance:



- 60° C to + 260° C

## Standard Length:

3 to 10 meters

					
int mm	kg/m	mm	mm	bar	bar
50	0.50	0.4	30.0	0.90	0.32
60	0.60	0.4	36.0	0.78	0.22
76	0.75	0.4	45.0	0.62	0.14
80	0.80	0.4	48.0	0.61	0.12
102	0.90	0.4	60.0	0.51	0.08
110	0.92	0.4	66.0	0.48	0.06
120	1.00	0.4	72.0	0.36	0.05
127	1.02	0.4	75.0	0.33	0.05
152	1.25	0.4	90.0	0.22	0.04
160	1.28	0.4	96.0	0.21	0.03
180	1.48	0.4	126.0	0.17	0.02
203	1.65	0.4	140.0	0.15	0.02
254	2.00	0.4	175.0	0.10	0.01
305	2.25	0.4	210.0	0.07	0.01
350	2.70	0.4	245.0	0.06	0.01
407	3.15	0.4	320.0	0.04	0.01
508	4.20	0.4	400.0	0.04	0.01

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
+91-79903 36570  
**S.D. Shah - Director**  
+91-90990 16044

 flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002