

HIGH TEMPERATURE CLIP HOSE - HT - 450

Temp. - 20°C to + 450°C




Structure:

Wall made of Single ply silver Vinyl coated fibreglass fabric. It is mechanically crimped in a continuous process. Fabric is locked around a coated steel wire by a metal strip formed into a clip. Metal strip acts as a wearstrip and offers outstanding external abrasion resistance.

Characteristics:

Tough and extremely flexible hose, Compressible, good resistance to high temperatures and chemicals.

Application

Automotive, Brick Kilns, Cold Air Supply, Diesel/Engine Exhaust, Exhaust Systems, Flame Retardant, Foundries, Garage Exhaust, Heater, Jet Fuel Vapor Venting, Pollution Control, Vehicle Exhaust Systems.





Temperature Resistance:

- 20°C to + 450°C

Size		Wall Thickness	Bend Radius	Compression Ration	Vacuun (PSI)	W.P. (PSI)	KG / Roll	Std. Length Meter
ID Inch	ID mm							
2	50	0.45	3	3:1	10	16	5	10
2 1/2	63	0.45	3	3:1	10	16	4.2	10
3	76	0.45	3	3:1	10	16	4.3	10
3 1/2	89	0.45	3	3:1	10	16	4.6	10
4	102	0.45	3.5	3:1	9	15	5.3	10
4 1/2	115	0.45	3.5	3:1	9	15	5.6	10
5	125	0.45	5	5:1	9	15	6.5	10
6	150	0.45	7	5:1	7	15	7.7	10
8	200	0.45	6	6:1	7	12	11.5	10
10	250	0.45	5	8:1	6	10	13.4	10
12	300	0.45	5	8:1	4	10	15.6	10

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002