

HIGH TEMPERATURE CLIP SILICON

Temp. - 60° C to + 300° C



Structure:

Light weight and very flexible Silicone ducting

Material:

Silicone coated glass fabric, silver-grey

Properties

Good temperature resistance, outer wear strip, flame retardant wall, excellent axial compressibility, good UV and ozone resistance, highly flexible

Application







Suction of hot fumes, gases or dust in all fields of industry

Temperature Resistance:



- 60° C to + 300° C

Standard Length:

3 to 10 meters

					
int mm	kg/m	mm	mm	bar	bar
50	0.40	0.4	30	0.85	0.32
60	0.50	0.4	36	0.68	0.22
76	0.60	0.4	45	0.47	0.14
80	0.62	0.4	48	0.43	0.13
102	0.65	0.4	60	0.3	0.08
110	0.70	0.4	66	0.25	0.07
120	0.72	0.4	72	0.22	0.06
127	0.80	0.4	75	0.21	0.05
152	0.90	0.4	90	0.16	0.04
160	0.94	0.4	96	0.14	0.03
180	1.00	0.4	108	0.12	0.02
203	1.21	0.4	120	0.1	0.02
254	1.70	0.4	175	0.07	0.01
305	2.13	0.4	210	0.05	0.01
350	2.50	0.4	245	0.04	0.01
407	3.10	0.4	280	0.03	0.01
508	4.15	0.4	400	0.02	0.01

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002