

# HOSE CLAMPS - SCREW CUFF - COUPLING

**M. S. & S.S.**



## WORM DRIVE SERRATED CLAMP

- ▶ Stainless and carbon steel material
- ▶ Trivalent & hexavalent passivated zinc plating
- ▶ useful for soft hose applications.

Standard: BS5315



## STAINLESS STEEL WORM DRIVE CLAMP

- ▶ Non- throbbing surfaces
- ▶ Clean punched perforations
- ▶ Application ranging from domestic to heavy industries.

Standard: SAE J1508 Type "F"



Ordering Code	Size mm	Min Dia mm	Max Dia mm
000	12	9	12
00M	16	12	16
00	20	14	20
0	22	16	22
100S	25	18	25
0X	28	20	28
1A	30	22	30
137S	35	25	35
1	38	30	38
1X	40	30	40
45A	45	32	45
2A	50	38	50
2	55	42	55
2X	60	45	60
3	70	50	70
75A	75	55	75
3X	80	60	80
4	90	70	90
4X	100	80	100
110A	110	90	110
5	115	95	115
5X	120	100	120
6	130	110	130
140A	140	125	140
575S	145	125	145
6X	160	140	160
7	180	160	180
8	200	180	200
9	230	205	230
10	250	230	250
11	280	260	280
12	300	280	300
13	330	305	330
14	356	330	356
15	375	354	375
16	400	375	400
18	450	425	450

Additional sizes are available as per enquiry.

**Pooja Shah - Sales**  
 +91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
 +91-79903 36570  
**S.D. Shah - Director**  
 +91-90990 16044

flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
 www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
 106, First Floor, Kailashpathi Chamber,  
 Nr. Sunrise Restaurant, Reid Road,  
 O/S Panchkuva Gate, Ahmedabad - 380 002



**M. S. & S.S.**

## S.S. / M.S BOLT HEAVY TYPE & O.H.T.C. HOSE CLAMP



**S. S. BOLT HEAVY TYPE HOSE CLAMPS 20 mm (Width)**

Size mm	Min Dia mm	Max Dia mm
225	225	250
250	250	270
300	310	340

Additional sizes are available as per enquiry.

**M. S. BOLT HEAVY TYPE HOSE CLAMPS 16mm (Width)**

Size mm	Min Dia mm	Max Dia mm
75	78	82
100	100	110
115	115	120
125	124	130

Additional sizes are available as per enquiry.

**S. S. BOLT HEAVY TYPE HOSE CLAMPS 16mm (Width)**

Size mm	Min Dia mm	Max Dia mm
30	31	35
35	39	43
40	47	52
50	47	55
60	59	64
75	70	75
80	77	82
85	82	87
90	90	95
100	100	110
125	120	130

Additional sizes are available as per enquiry.



## S.S. BRIDGE CLAMP

One-piece hose clamp, consisting of folded bridge, housing and clamp band. Available for hoses in right or left hand construction

Material: Galvanized steel

Band Width : 12 mm

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458

**Chirag Shah - Technical**  
+91-79903 36570

**S.D. Shah - Director**  
+91-90990 16044

flexaflexhoses@gmail.com

www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002

# HOSE CLAMPS - SCREW CUFF - COUPLING



**M. S. & S.S.**

## Bridge Clamping range

95-115, 105-125, 115-135, 125-145, 135-155, 145-165, 155-175, 165-185, 175-195, 185-205, 195-215, 205-225,  
215-235, 225-245, 235-255, 245-265, 265-285, 295-315, 315-335, 345-365, 365-385, 395-415, 445-465, 495-515



**Screw cuff**

Black screw cuff with a standard thread in different diameters. Other colours on request.



**Standard crip cuff**

Black screw cuff with different threads and out of various materials. Other colours on request.



**Coupling**

Screw cuff for different hoses and diameters.



**Reducer**

For connecting light and middle weight

Technical data	
Dia. (mm)	reduced to dia. (mm)
63	50
71	50/63
75	50
80	50/63/71
85	71
90	71/80
100	50/63/71/75/80/90
112	71/75/80/90/100
125	71/75/80/90/100/112
140	71/80/90/100/112/125
150	71/80/90/100/112/125/140
160	71/80/90/100/112/125/140/150
180	71/80/90/100/112/125/140/150/160
200	80/90/100/112/125/140/150/160/180
224	90/100/112/125/140/150/160/180/200
250	100/112/125/140/150/160/180/200/224
280	112/125/140/150/160/180/200/224/250
300	125/140/150/160/180/200/224/250/280
315	140/150/160/180/200/224/250/280/300
355	150/160/180/200/224/250/280/300/315
400	160/180/200/224/250/280/300/315/355



**Hose Connector**

For the connection and extension of light and middle weight.

Technical data
63
71
80
90
100
112
125
140
150
160
180
200
224
250
280
300
315
355
400
450
500
560
600

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
+91-79903 36570  
**S.D. Shah - Director**  
+91-90990 16044

flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002