

PVC SELF SUPPORTING HOSE



Temp. : -10°C to +70°C



Structure:

Interlocking rigid PVC profile by rigid PVC.
Flame Retardant.

Properties:

- Self-supporting
- Simple increase or reduction of size
- Jointing of lengths
- Good resistance to acids, alkalis, and chemicals
- maintain shape
- Flame-retardant according to UL94-HB

Applications:

- For air, fume extraction and liquid supply under low pressure
- For conveyance of powder, granules and dust extraction
- For wood dust extraction
- Portable air conditioner venting hose

Temperature range:

-10°C to 70°C




Colour:

Grey / Black



Standard Length :

5 meter



 int mm	 out mm	 Std.len.
51	57	5
65	71	5
75	82	5
90	97	5
100	107	5
125	133	5
150	158	5
200	208	5

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002