



Structure:

Suction and transport hose, inside outside smooth, tough and flexible, vacuum and compression resistant and with high axial strength

Material

Polyvinyl Chloride Food Grade - FDA as per US FDA 21 CFR 175.300 free from all hazardous plasticizers, stabilizers and other additives like lead, Paraffin, phthalates etc.

Reinforcement:

Spring steel wire reinforced.

Temperature range:

70°C






Colour:

Transparent

Applications:

Vacuum Lines of auto loaders in plastic processing industries like injection moulding blow moulding, extrusion for conveying resin and plastic granules, low temperature food grade material, powder and liquids in food processing and pharmaceutical industry, draining sewage and water. Used as oil drains for machineries and also other vacuum lines in different industries. Widely used for drinking water, edible oil, milk and other liquids in food and pharma sectors.



				
ID mm	OD mm	mm	bar	mbar
25.4	32	128	4.0	850
32	39	164	4.0	850
38.5	49.5	188	4.4	935
51.8	62	256	4.4	880
65	76	308	3.78	735
77.3	91	360	3.78	735

★ 100% free and safe from hazardous chemicals like lead, paraffin, phthalates.

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table.

In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advice you.

Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 27°C)

Pooja Shah - Sales

+91-99784 42215 | +91-70690 96458

Chirag Shah - Technical

+91-79903 36570

S.D. Shah - Director

+91-90990 16044



flexaflexhoses@gmail.com



www.flexaflexhoses.com

www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL

106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002