

CEMENT GROUTING HOSE CONCRETE TRANSFER HOSE



Structure:

- Inner Tube - special natural rubber
- Reinforcement - High tensile synthetic yarn twin copper wires ensure reliable conductivity
- Out Cover - Special Natural Rubber

Applications:

For pumping concrete with high head pressure from concrete boom truck and as a discharge hose on the delivery end of high pressure concrete pumps. Ideal for handling wet concrete plaster or grout mixture.

Temperature range:

-40°C to +70°C

int mm	out mm	W.P. Kg/cm ²	B.P. Kg/cm ²	mm	in. Hg
63.5	89	85	255	20.0	10.0
76.2	100	85	255	20.0	10.0

CEMENT GROUTING HOSE / CONCRETE TRANSFER HOSE



int mm	out mm	W.P. bar	B.P. bar
25	31	10	30
31	38	10	30
38	48	10	30
50	62	10	30
63	75	10	30
75	89	10	30
100	116	10	30

Standard : Exceeds IS 5137 : 1990

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002