

# ROCK DRILL HOSE WIRE BRAIDED

**flexaflex**



## Structure:

- Inner Tube - Special NBR rubber with Oil / Mist / Heat resistant.
- Reinforcement - Single braided high tensile wire
- Cover - Abrasion, heat and mist resistant Nitrile rubber

## Applications:



Heavy duty applications in mining and jack hammer applications in construction crusher zones.

## Temperature range:

-30°C to +82°C

				
int mm	out mm	W.P. bar	B.P. bar	mm
20.0	27.5	60	240	152
25.0	36.5	50	200	201
31.0	44.0	50	200	254
38.0	50.0	50	200	304
50.0	63.5	40	160	355
63.0	80.0	40	160	762
75.0	94.0	40	150	914

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
+91-79903 36570  
**S.D. Shah - Director**  
+91-90990 16044

 flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002