

VacuDuc

PVC STEEL WIRE HOSE

THUNDER HOSE - NON TOXIC - FOOD GRADE

flexAflex



Structure:

Suction and transport hose, inside outside smooth, tough and flexible, vacuum and compression resistant and with high axial strength

Material

Polyvinyl Chloride - Non Toxic Food Grade,

Reinforcement:

Spring steel wire reinforced.

Applications:

Vacuum Lines of auto loaders in plastic processing industries like injection moulding blow moulding, extrusion for conveying resin and plastic granules, low temperature food grade material, powder and liquids in food processing and pharmaceutical industry, draining sewage and water. Used as oil drains for machineries and also other vacuum lines in different industries. Widely used for drinking water, edible oil, milk and other liquids in food and pharma sectors.

Temperature range:

70°C

Colour:

Transparent



Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com






FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002

VacuDuc

PVC STEEL WIRE HOSE

THUNDER HOSE - NON TOXIC - FOOD GRADE

flexAflex

 ID mm	 OD mm	 mm	 bar	 mbar
10	16	64	7.0	850
12	18	72	6.0	850
13	19	76	6.0	850
14	20	80	6.0	850
16	22	90	5.0	850
18	24	98	5.0	850
19	25	100	5.0	850
20	26	104	5.0	850
22	28	112	5.0	850
25	32	128	4.0	850
30	38	152	4.0	850
32	41	164	4.0	850
35	44	176	4.0	850
38	47	188	4.0	850
40	50	200	4.0	850
42	52	208	4.0	800
45	55	220	4.0	800
48	58	232	4.0	800
50	60	256	4.0	800
60	72	288	3.6	800
63	75	300	3.6	800
65	77	308	3.6	700
70	83	332	3.6	700
75	89	356	3.6	700
76	90	360	3.6	700
80	94	372	3.6	700
90	104	416	3.0	700
102	116	464	2.4	700
127	142	470	2.4	700
152	168	490	2.4	700
203	223	510	2.4	700

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table.

In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you.

Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 27°C)

Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458
Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

 flexaflexhoses@gmail.com
 www.flexaflexhoses.com
www.hosesmarket.com

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002