

# VACUUM LIFT HOSE



**Temp. : -35°C to +135°C**



## Structure:

Wall made from Neoprene(CR) coated fiberglass fabric, reinforced with spring steel wire.

## Characteristics:

Compressible hose : 3:1

## Applications:

Specially designed for lifting heavy goods, as a component of vacuum lifting systems.

Temperature:  
-35°C to 135°C

Colour:  
Dark Blue

Wall Thickness :  
0.7 - 1.2 mm

Standard Length :  
500 mm to 4000 mm



Bending radius:  
Same as Dia

Right rotation:  
Yes



I.D. mm	Wire. mm	Pitch. mm	KG Per Mtr.	Lift KG
80	1.4	12	0.81	20
102	1.55	12-13	1.02	30
120	1.8	12-14	1.20	40
140	2	11-14	1.35	50
160	2.25	11	1.80	60
178	2.5	11	2.12	80
203	2.5	11	2.73	100
229	3	11	3.26	120
250	3	11	3.56	160
305	3.5	11	3.80	270

**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458  
**Chirag Shah - Technical**  
+91-79903 36570  
**S.D. Shah - Director**  
+91-90990 16044

 flexaflexhoses@gmail.com  
 www.flexaflexhoses.com  
www.hosesmarket.com

**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002