



Flexaflex Hoses International is a trading company, Importing German Flexible Hoses and supplying to various OEMs and actual users of wood working machineries throughout India and other neighboring countries.

**THE ULTIMATE DESTINATION
FOR INDUSTRIAL FLEXIBLE HOSES**

**e-Mail:
flexaflexhoses@gmail.com**

**Web:
www.flexaflexhoses.com
www.hosesmarket.com**

WOOD INDUSTRY - HOSES

For Wood working machineries like CNC Routers/ Boring/Engraving machines – Edge benders/Panel saw/ Planers / Rip saw / Finger jointing / Dust collectors and many more.

Products



Contact US

Pooja Shah - Sales
+91-99784 42215
+91-70690 96458

Chirag Shah - Technical
+91-79903 36570

S.D. Shah - Director
+91-90990 16044

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002



**PU HOSE - LIGHT DUTY
Ether Grade**

**Wall Thick.
0.4 mm**

**Temp. -40°C to +100°C
(Short-term: +125°C)**



**PU HOSE - HEAVY DUTY
Ether Grade**

**Wall Thick.
0.6 / 0.7 / 1 / mm**

**Temp. -40°C to +100°C
(Short-term: +125°C)**



**PU HOSE
EXTRA HEAVY DUTY
Ether Grade**

**Wall Thick.
1.2 & 1.4 mm**

**Temp. -40°C to +100°C
(Short-term: +125°C)**



**PU HOSE - PERMANENTLY
ANTISTATIC AND FLAME
RETARDANT**

**Wall Thick.
0.4/0.6/0.7/1/1.4/2mm**

**Temp. -40°C to +100°C
(Short-term: +125°C)**



**PVC FLEXIBLE DUCT HOSE
GREY**

Temp. 60°C



**PU HOSE WITH RIGID HELIX
Serie 3PUR S - AL
FOOD GRADE**

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C



**PVC STEEL WIRE HOSE
THUNDER HOSE**

FOOD GRADE

Wall Thick. 3.5 to 7 mm

Temp. 70°C



**PU HOSE WITH RIGID HELIX
Serie 3PUR M - AL - ANT**

FOOD GRADE / ANTISTATIC

Wall Thick. 0.75 to 1mm

Temp. -30°C to +80°C



**SILICON DOUBLE
LAYER HOSE**

Wall Thick. 1 mm

**Temp. -70°C to +270°C
(Short time 300°C)**



**SILICON DOUBLE
LAYER HOSE**

Wall Thick. 0.7 mm

**Temp. -70°C to +270°C
(Short time 300°C)**



**VACUUM LIFT HOSE
BLACK - ORANGE**

Range : 100, 120, 150, 160, 180, 200mm

Temp: 85°C



**POLYESTER FABRIC HOSE
PVC COATED**

**UV / Flame Resistant / Antistatic
Grey / Blue / Yellow / White**

Wall Thick. 0.35 / 0.4 / 0.5

Temp. -30°C to +70°C




**PVC BRAIDED HOSES
TRANSPARENT (HEAVY DUTY)**

Wall Thick. 2.5 to 8 mm

Range : 6 mm to 76 mm


W. P. 6kg/cm² to 25kg/cm²

Temp. 70°C



**ALUMINIUM FOIL HOSE
LIGHT / HEAVY Types**

Temp. 100°C & 250°C



**ALUMINIUM SEMI-RIGID
AIR DUCT**

Temp.150°C



**EVA PROFILE HOSE
INDUSTRIAL VACUUM
CLEANER HOSE
SWIMMING POOL HOSE**

Temp. -50°C up to +60°C



**VAT-ELASTIC HOSE
VACUUM CLEANER HOSE**

WET AND DRY FLOOR CARE

Wall Thick. 0.5 mm

Temp. 0°C up to +85°C



**PVC SUCTION & DELIVERY HOSE
HEAVY DUTY GREY**

Range: 40 mm to 300 mm

W. P. 2.5kg/cm² to 8kg/cm²

B. P. 6kg/cm² to 25kg/cm²

Temp. 60°C



**PVC SUCTION & DELIVERY HOSE
GREEN - MEDIUM DUTY**

Range: 20 mm to 100 mm

W. P. 3.5kg/cm² to 7kg/cm²

B. P. 11kg/cm² to 24kg/cm²

Temp. 60°C



**HYDRAULIC HOSES
SAE R1 AT**

Range :6.3 mm to 50.8 mm

W.P. 40 to 230 kg/cm²

B.P. 163 to 920 kg/cm²

Temp. -40°C to +100°C



**HYDRAULIC HOSES
SAE R2 AT**

Range :6.3 mm to 50.8 mm

W.P. 82 to 400 kg/cm²

B.P. 325 to 1630 kg/cm²

Temp. -40°C to +100°C



AIR AND WATER HOSE

Range : 12.5 mm to 100 mm ID

W.P. 12 kg/cm²

Temp. -30°C to +82°C

I.S. 446 Type - I / I.S. 444 Type - II



PNEUMATIC TOOL HOSE

Range : 6.3 mm to 50 mm ID

W.P. 14 kg/cm²

Temp. -30°C to +82°C

I.S. 446 : 1980 Type II



**PNEUMATIC TUBE
(PU TUBE)**

W.P. 6 to 10 kg/cm²



**HIGH PRESSURE AIR
CLEANING HOSES**

Range :8.5 mm to 20 mm

W.P. 30 to 60 kg/cm²

B.P. 120 to 225 kg/cm²



M.S. HOSE CLAMP



S.S. HOSE CLAMP



S.S. / M.S BOLT HEAVY TYPE
& O.H.T.C. HOSE CLAMP



S.S. BRIDGE CLAMP



Coupling
Screw cuff for different hoses
and diameters.



Standard crip cuff
Black screw cuff with different threads
and out of various materials. Other
colours on request.



Hose Connector