

# flexaflex

FLEXAFLEX HOSES INTERNATIONAL

THE ULTIMATE DESTINATION  
FOR INDUSTRIAL FLEXIBLE HOSES

HOSES FOR FLOOR CARE,  
DUST COLLECTION &  
POWDER CONVEYING.



## Contact



**Pooja Shah - Sales**

+91-99784 42215

+91-70690 96458



**Chirag Shah - Technical**

+91-79903 36570



**S.D. Shah - Director**

+91-90990 16044



**flexaflexhoses@gmail.com**



**FLEXAFLEX HOSES INTERNATIONAL**

106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002

## OUR PROFILE

Flexaflex Hoses International are the Leading Hose Suppliers in Ahmedabad, Gujarat, India actively engaged in importing technical industrial hoses from Germany and Europe, Taiwan & China and catering pan India.



[www.flexaflexhoses.com](http://www.flexaflexhoses.com)

[www.hosesmarket.com](http://www.hosesmarket.com)





**EVA VACUUM CLEANER HOSE**

**Industrial vacuum cleaner & Swimming pool hose**

**Temp. -50°C up to +60°C**



**VAT-ELASTIC HOSE VACUUM CLEANER HOSE**

**WET AND DRY FLOOR CARE**

**Wall Thick. 0.5 mm**

**Temp. 0°C up to +85°C**



**PVC VACUUM HOSE - FLEX ANT**

**FOOD GRADE / PHTHALATE FREE / ANTISTATIC**

**Wall Thick . 3 to 6.5 mm**

**Temp. 0°C up to +60°C**




**PU HOSE WITH RIGID PLASTIC HELIX**

**FOOD GRADE**

**Wall Thick. 0.75 to 1mm**

**Temp. -30°C to +80°C**

**POWDER CONVEYING**



**PU HOSE WITH RIGID PLASTIC HELIX**

**FOOD GRADE / ANTISTATIC**

**Wall Thick. 0.75 to 1mm**

**Temp. -30°C to +80°C**

**POWDER CONVEYING**



**PVC DUCT HOSE**

**GREY**


**Temp. 60°C**



**PVC DUCT HOSE**

**TRANSPARENT**

**Temp. 60°C**



**PU HOSE - LIGHT DUTY Ether Grade**

**Wall Thick. 0.4 mm**

**Temp. -40°C to +100°C (Short-term: +125°C)**



**PU HOSE - HEAVY DUTY Ether Grade**

**Wall Thick.**

**0.6/0.7/0.9/1/ 1.2/1.4 /1.5 mm**

**Temp. -40°C to +100°C (Short-term: +125°C)**



**PU HOSE - EXTRA HEAVY DUTY Ether Grade**

**Wall Thick. 2.5 mm**

**Temp. -40°C to +100°C (Short-term: +125°C)**




**PU HOSE - PERMANENTLY ANTISTATIC AND FLAME RETARDANT**

**Wall Thick.**

**0.4/0.6/0.7/1/1.4/2mm**

**Temp. -40°C to +100°C (Short-term: +125°C)**

**( SMARTFLEX )**



**FLEXADUX HT PU POLYURETHANE HOSE FOR HIGH TEMPERATURE APPLICATIONS**

**Wall Thick . 0.7/1/1.4 mm**

**Temp. -40°C to +145°C (Short-term: +165°C)**




**PVC STEEL WIRE HOSE THUNDER HOSE**

**FOOD GRADE**

**Wall Thick. 3.5 to 7 mm**

**Temp. 70°C**




**VACUUM LIFT HOSE GERMAN**

**Wall Thick. 0.7 - 1.2 mm**

**Range : 80 to 305 mm**

**Temp: -35°C to 135°C**

**Colour: Black & Dark Blue**



**PVC SEMI RIGID SELF SUPPORTING HOSE**

**Colour: Grey**  
**Range : 51 to 200 mm ID**  
**Temp. -10°C to 70°C**



**PVC BRAIDED HOSES TRANSPARENT (HEAVY DUTY)**  
**Wall Thick. 2.5 to 8 mm**  
**Range : 6 mm to 76 mm**  
**W. P. 6kg/cm<sup>2</sup> to 25kg/cm<sup>2</sup>**  
**Temp. 70°C**



**SILICONE DUCT HOSE DOUBLE LAYER**

**Wall Thick. 0.8/ 1 mm**  
**Temp. -70°C to +300°C**



**SILICONE DUCT HOSE DOUBLE LAYER**

**HOT PET CONVEYANCE**  
**Wall Thick. 5 mm**  
**Temp. -60°C to +200°C**



**THERMOPLASTIC RUBBER HOSE**  
**TPR - HOSE**

**Temp. -40°C to +135°C**  
**(short term up to +150°C)**



**HIGH TEMPERATURE (HT 450) GLASS FABRIC CLIP HOSE**

**Wall Thick. 0.45 mm**  
**Temp. -20°C to +450°C**



**POLYESTER FABRIC HOSE PVC COATED**

**UV / Flame Resistant / Antistatic**  
**Grey / Blue / Yellow / White**  
**Wall Thick. 0.35 / 0.4 / 0.5**  
**Temp. -30°C to +70°C**



**PP Air Hose**

**Colour: Ivory**  
**Temp: -20°C to +80°C**



**S.S. 304 GRADE BRIDGE CLAMP LHS & RHS**



**PNEUMATIC FITTINGS AND Standard Cylinder A16, A17**



**S.S. / M.S BOLT HEAVY TYPE & O.H.T.C. HOSE CLAMP**



**M.S. & S.S HOSE CLAMP**



**Hose Connector**



**Coupling**

**Screw cuff for different hoses and diameters.**



**Screw cuff**

