

THE ULTIMATE DESTINATION FOR INDUSTRIAL FLEXIBLE HOSES




FLEXAFLEX HOSES INTERNATIONAL

GERMAN HOSES FOR HEATING / VENTILATION AND AIR CONDITIONING

OUR PROFILE

Flexaflex Hoses International are the Leading Hose Suppliers in Ahmedabad, Gujarat, India actively engaged in importing technical industrial hoses from Germany and Europe, Taiwan & China and catering pan India.



Contact



Pooja Shah - Sales

+91-99784 42215

+91-70690 96458



Chirag Shah - Technical

+91-79903 36570



S.D. Shah - Director

+91-90990 16044



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL

106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002






**POLYESTER FABRIC HOSE
PVC COATED
FIRE RETARDANT
BLACK**
Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - UV RESISTANT
Heavy Duty - Fire Retardant**
Range: 38 mm to 1000 mm
Wall Thick.: 0.5 mm
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - UV RESISTANT
Heavy Duty
Antistatic and Fire Retardant**
Range: 38 mm to 1000 mm
Wall Thick.: 0.5 mm
Temp. -20°C to 70°C




**POLYESTER FABRIC HOSE
PVC COATED
Fire Retardant /
Outer Wearstrip Profile**
Range: 150 mm to 3500 mm
Temp. -20°C to 80°C



**HVAC - Ventilation Hose
Yellow Fabric Hose**
UV / Flame Resistant
Range: 38 mm to 609 mm
Wall Thick. 0.5 mm
Temp. -20°C to +70°C



**POLYESTER FABRIC HOSE
PVC COATED
UV Resistant and Fire Retardant
GREY - LIGHT**
Range: 50 mm to 600 mm
Wall Thick.: 0.25 / 0.3
Temp. -20°C to 70°C



**POLYESTER FABRIC HOSE
PVC COATED - BLUE - HEAVY**
UV Resistant and Fire Retardant
Colour: Blue / Black / Grey / Yellow
Range: 38 mm to 1000 mm
Wall Thick.: 0.4 mm
Temp. -20°C to 70°C




**SILICONE DUCT HOSE
DOUBLE LAYER**
Wall Thick.
0.8 / 1 / 5 mm
Temp. -70°C to +300°C



**PU HOSE - LIGHT DUTY
Ether Grade**
Wall Thick.
0.4 mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**PU HOSE - HEAVY DUTY
Ether Grade**
Wall Thick.
0.6 / 0.7 / 0.9 / 1 / 1.2 mm
Temp. -40°C to +100°C
(Short-term: +125°C)



**FLEXADUX HT PU
POLYURETHANE HOSE FOR HIGH
TEMPERATURE APPLICATIONS**
Wall Thick . 0.7/1/1.4 mm
Temp. -40°C to +145°C
(Short-term: +165°C)



**PU HOSE - PERMANENTLY
ANTISTATIC AND FLAME RETARDANT**
Wall Thick.
0.4/0.6/0.7/1/1.4/2mm
Temp. -40°C to +100°C
(Short-term: +125°C)
(SMARTFLEX)



**PU HOSE FDA APPROVED
FLEXADUX P7 L & M PU PAS FOOD**
FOOD GRADE - FDA APPROVED
PERMANENTLY ANTISTATIC
WITH SS 304 WIRE
Wall Thick . 0.7/ 1.4 mm
Temp. -40°C to +100°C (Short-term: +125°C)
(PAS FOOD)



**THERMOPLASTIC
RUBBER HOSE
TPR HOSE**
Temp. -40°C to +135°C
(short term up to +150°C)



**ALUMINIUM FOIL HOSE
LIGHT / HEAVY Types**
Temp. 100°C & 250°C



**ALUMINIUM FOIL HOSE
WITH INSULATION**
Temp. 150°C



PVC DUCT HOSE
GREY
Temp. 60°C




AC VENT. HOSE
Range: 25 mm to 250 mm
Temp. -20°C to +80°C



SEMI INSULATED ALUMINIUM FOIL HOSE
Temp. 150°C



ALUMINIUM SEMI-RIGID AIR DUCT
Temp. 150°C



EVA VACUUM CLEANER HOSE
Industrial vacuum cleaner & Swimming pool hose
Temp. -50°C up to +60°C



VAT-ELASTIC HOSE VACUUM CLEANER HOSE
WET AND DRY FLOOR CARE
Wall Thick. 0.5 mm
Temp. 0°C up to +85°C



HYDRAULIC HOSES SAE R1 AT
Range : 6.3 mm to 50.8 mm
W.P. 40 to 230 kg/cm²
B.P. 163 to 920 kg/cm²
Temp. -40°C to +100°C



FLEXIBLE METAL HOSES S.S. CORRUGATED FLEXIBLE HOSES
Stainless steel
AISI 304, AISI 321 and AISI 316L
Temp. -270°C to +600°C
EN ISO 10380



PVC SELF SUPPORTING HOSE
AC VENT. HOSE
Colour: Grey
Range : 51 to 200 mm ID
Temp. -10°C to 70°C



PVC BRAIDED HOSES TRANSPARENT (HEAVY DUTY)
Wall Thick. 2.5 to 8 mm
Range : 6 mm to 76 mm
W. P. 6kg/cm² to 25kg/cm²
Temp. 70°C



PNEUMATIC TUBE PU TUBE & FITTINGS
W.P. 6 to 10 kg/cm²



PVC SUCTION & DELIVERY HOSE GREEN - MEDIUM DUTY
Range : 20 mm to 100 mm
W. P. 3.5kg/cm² to 7kg/cm²
B. P. 11kg/cm² to 24kg/cm²
Temp. 60°C



THERMOPLASTIC RUBBER HOSE AIR / PNEUMATIC
Range : 6 mm to 50 mm
W.P. 14 to 22 kg/cm²



THERMOPLASTIC RUBBER HOSE WATER - HOSE
Range : 12.5 / 20 / 25 mm
W.P. 10 kg/cm²



HIGH PRESSURE AIR CLEANING HOSE
Range : 8.5 mm to 20 mm
W.P. 30 to 60 kg/cm²
B.P. 120 to 225 kg/cm²



S.S. BRIDGE CLAMP RHS & LHS



M.S. & S.S. HOSE CLAMP

S.S. / M.S. BOLT HEAVY TYPE & O.H.T.C. HOSE CLAMP



Coupling

Standard strip cuff

Reducer

Hose Connector