



Flexaflex Hoses International

THE ULTIMATE DESTINATION
FOR INDUSTRIAL FLEXIBLE HOSES

e-mail:

flexaflexhoses@gmail.com

Web :

www.flexaflexhoses.com
www.hosesmarket.com



**IMPORTER OF
FLEXIBLE HOSES**



For Auto loaders, Hopper dryers, Metallized and Multilayer film plants, Extrusion, Flexographic printing machine, Rotogravure printing machine, Offset printing machine, Blow moulding, Packaging industry, PVC, HDPE, CPVC, PP Pipe manufacturing, Masterbatch industry, Speciality compounds, Food and Pharma.

Contact

Pooja Shah - Sales
+91-99784 42215
+91-70690 96458

Chirag Shah - Technical
+91-79903 36570
S.D. Shah - Director
+91-90990 16044

FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002




PU HOSE - HEAVY DUTY
Ether Grade
FOOD GRADE
 Wall Thick.
 0.6/ 0.8/0.9/1/1.2 mm
 Temp. -40°C to +100°C
 (Short-term: +125°C)



PU HOSE - HEAVY DUTY
Ether Grade
NON TOXIC
 Wall Thick.
 0.7/ 1 / 1.4/1.5 mm
 Temp. -40°C to +100°C
 (Short-term: +125°C)



PU HOSE - EXTRA HEAVY DUTY
Ether Grade
FOOD GRADE / NON TOXIC
Auto Loader Hose
 Wall Thick. 2.5 mm
 Temp. -40°C to +100°C
 (Short-term: +125°C)



PVC STEEL WIRE HOSE
THUNDER HOSE
FOOD GRADE
Auto Loader Hose
 Wall Thick. 3.5 to 7 mm
 Temp. 70°C



PVC VACUUM HOSE - FLEX ANT
Food Grade
Phthalate Free / Anti-Static
Auto Loader Hose
 Metallized and Multilayer Film Plants,
 Wall Thick 3 to 6.5 mm
 Temp. 0°C up to +60°C



SILICONE DUCT HOSE
DOUBLE LAYER
 Wall Thick. 0.8 mm
 Temp. -70°C to +300°C



SILICONE DUCT HOSE
DOUBLE LAYER
HOT PET GRANULES
 Wall Thick. 1 mm
 Temp. -70°C to +300°C



SILICONE DUCT HOSE
HOT PET CONVEYANCE
HOT PET GRANULES
 Wall Thick 5 mm
 Temp. -60°C to +200°C



THERMOPLASTIC RUBBER HOSE
TPR HOSE
 Wall Thick. 0.65 mm
 Temp. -40°C to +135°C
 (Short time 150°C)



HIGH TEMPERATURE (HT 450)
GLASS FABRIC CLIP HOSE
 Wall Thick. 0.45 mm
 Temp. -20°C to +450°C



PVC TRANSPARENT NON TOXIC HOSE
"DUTRON ANT COPPER"
FOOD GRADE
Auto Loader Hose
 W. P. 3.5kg/cm² to 7kg/cm²
 B. P. 11kg/cm² to 23kg/cm²
 Temp. 60°C



PVC DUCT HOSE
GREY
 Temp. 60°C



PVC DUCT HOSE
TRANSPARENT
 Temp. 60°C




PU HOSE WITH RIGID
PLASTIC HELIX
FOOD GRADE
 Wall Thick. 0.75 to 1mm
 Temp. -30°C to +80°C

POWDER CONVEYING



PU HOSE WITH RIGID PLASTIC HELIX
FOOD GRADE / ANTISTATIC
 Wall Thick. 0.75 to 1mm
 Temp. -30°C to +80°C



POLYESTER FABRIC HOSE PVC COATED
 UV / Flame Resistant / Antistatic
 Grey / Blue / Yellow / White
 Wall Thick. 0.35 / 0.4 / 0.5
 Temp. -30°C to +70°C



HVAC - Ventilation Hose Yellow Fabric Hose
 UV / Flame Resistant
 Wall Thick. 0.5 mm
 Temp. -20°C to +70°C



EVA VACUUM CLEANER HOSE
Industrial vacuum cleaner & Swimming pool hose
 Temp. -50°C to +60°C



VAT-ELASTIC HOSE VACUUM CLEANER HOSE
WET AND DRY FLOOR CARE
 Wall Thick. 0.5 mm
 Temp. 0°C to +85°C




PU HOSE FDA APPROVED FLEXADUX P7 L & M PU PAS FOOD
FOOD GRADE - FDA APPROVED PERMANENTLY ANTISTATIC WITH SS 304 WIRE
 Wall Thick . 0.7/ 1.4 mm
 Temp. -40°C to +100°C (Short-term: +125°C)
(PAS FOOD)



FLEXADUX HT PU POLYURETHANE HOSE FOR HIGH TEMPERATURE APPLICATIONS
 Wall Thick . 0.7/1/1.4 mm



PU HOSE - PERMANENTLY ANTISTATIC AND FLAME RETARDANT
 Wall Thick. 0.4/0.6/0.7/1/1.4/2mm
 Temp. -40°C to +100°C (Short-term: +125°C)
(SMARTFLEX)



PU HOSE ELECTRICALLY CONDUCTIVE FLEXADUX P7 M PU EL
 Wall Thick. 1.4 mm
 Temp. -40°C to 100°C



VACUUM LIFT HOSE GERMAN
 Wall Thick. 0.7 - 1.2 mm
 Range : 80 to 305 mm
 Temp: -35°C to 135°C
 Colour: Black & Dark Blue



FLEXIBLE METAL HOSES S.S. CORRUGATED FLEXIBLE HOSES
 Stainless steel
 AISI 304, AISI 321 and AISI316L
 Temp. -270°C to +600°C
 EN ISO 10380



HYDRAULIC HOSES SAE R1 AT
 Range :6.3 mm to 50.8 mm
 W.P. 40 to 230 kg/cm²
 B.P. 163 to 920 kg/cm²
 Temp. -40°C to +100°C




HYDRAULIC HOSES SAE R2 AT
 Range :6.3 mm to 50.8 mm
 W.P. 82 to 400 kg/cm²
 B.P. 325 to 1630 kg/cm²
 Temp. -40°C to +100°C



PNEUMATIC TOOL HOSE
 Range : 6.3 mm to 50 mm ID
 W.P. 14 kg/cm²
 Temp. -30°C to +82°C
 I.S. 446 : 1980 Type II



AIR AND WATER HOSE
 Range : 12.5 mm to 100 mm ID
W.P. 12 kg/cm²
 Temp. -30°C to +82°C
 I.S. 446 Type - I / I.S. 444 Type - II



**PVC BRAIDED HOSES
 TRANSPARENT (HEAVY DUTY)**
 Wall Thick. 2.5 to 8 mm
Range : 6 mm to 76 mm
W. P. 6kg/cm² to 25kg/cm²
Temp. 70° C



**PVC SUCTION & DELIVERY HOSE
 GREEN - MEDIUM DUTY**
Range : 20 mm to 100 mm
W. P. 3.5kg/cm² to 7kg/cm²
B. P. 11kg/cm² to 24kg/cm²
Temp. 60°C



**PVC SUCTION & DELIVERY HOSE
 HEAVY DUTY GREY**
Range : 25 mm to 300 mm
W. P. 2.5kg/cm² to 8kg/cm²
B. P. 6kg/cm² to 25kg/cm²
Temp. 60°C



**THERMOPLASTIC RUBBER HOSE
 AIR / PNEUMATIC**
 Range : 6 mm to 50 mm
W.P. 14 to 22 kg/cm²



**THERMOPLASTIC RUBBER HOSE
 WATER - HOSE**
 Range : 12.5 / 20 / 25 mm
W.P. 10 kg/cm²



**HIGH PRESSURE AIR
 CLEANING HOSES**
 Range : 8.5 mm to 20 mm
W.P. 30 to 60 kg/cm²
B.P. 120 to 225 kg/cm²



**PNEUMATIC TUBE
 (PU TUBE)**
W.P. 6 to 10 kg/cm²



**S.S. 304 GRADE
 BRIDGE CLAMP
 LHS & RHS**



**PNEUMATIC FITTINGS
 AND Standard
 Cylinder A16, A17**



**S.S. / M.S BOLT HEAVY TYPE
 & O.H.T.C. HOSE CLAMP**



M.S. & S.S HOSE CLAMP



Hose Connector



Coupling

Screw cuff for different hoses
 and diameters.



Screw cuff

