



FLEXAFLEX HOSES INTERNATIONAL
Ahmedabad



Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458



Chirag Shah - Technical
+91-79903 36570



S.D. Shah - Director
+91-90990 16044

FLEXACIER STD FOOD



Structure:

Flexible hose made out of soft phthalatefree food grade PVC wall in accordance with the modified EU regulation 10/2011 (simulants A, B, C, D1) and CE 1935/2004, reinforced with galvanized steel helix.

Properties

Smooth inside, smooth outside.

Temperature range:

-5°C to +65°C

Standard Color:

Transparent with galvanised steel spiral

Applications:

Designed for standard duty suction and delivery of **high quality liquids and foodstuffs, including alcohol up to 50% in industry, agriculture, irrigation, water supply.**

Vacuum Lines of auto loaders in plastic processing industries like injection moulding blow moulding, extrusion for conveying resin and plastic granules, low temperature food grade material, powder and liquids in food processing and pharmaceutical industry, draining sewage and water. Used as oil drains for machineries and also other vacuum lines in different industries. Widely used for drinking water, edible oil, milk and other liquids in **food and pharma sectors.**

ID mm	OD mm	Bending Radius mm	Pressure bar	Vacuum mbar	Weight kg/m	Std. Length Meter
20	26.8	72	7.0	0.95	0.330	30
25	33.0	90	7.0	0.95	0.480	30
30	38.5	110	6.0	0.95	0.625	30
32	40.4	115	6.0	0.95	0.640	30
38	48.0	130	6.0	0.90	0.800	30
40	51.0	160	6.0	0.90	0.900	30
45	57.0	170	6.0	0.90	1.140	30
51	63.0	180	5.0	0.90	1.260	30
55	67.0	200	5.0	0.85	1.520	30
60	72.0	230	4.0	0.85	1.660	30
63	75.0	250	4.0	0.85	1.740	30
70	83.0	280	4.0	0.85	2.150	30



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002



FLEXAFLEX HOSES INTERNATIONAL
Ahmedabad



Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458



Chirag Shah - Technical
+91-79903 36570



S.D. Shah - Director
+91-90990 16044

ID mm	OD mm	Bending Radius mm	Pressure bar	Vacuum mbar	Weight kg/m	Std. Length Meter
76	89.0	330	4.0	0.85	2.300	30
80	93.0	350	3.5	0.85	2.450	30
90	103	380	3.0	0.85	2.750	30
102	116	400	3.0	0.85	3.340	30
105	121	420	3.0	0.85	3.700	30
110	126	430	2.5	0.85	3.800	20
120	136	450	2.0	0.85	4.200	20
127	140	450	2.0	0.85	5.000	20
152	167	500	2.0	0.85	6.000	20



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002