



FLEXAFLEX HOSES INTERNATIONAL
Ahmedabad



Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458



Chirag Shah - Technical
+91-79903 36570



S.D. Shah - Director
+91-90990 16044

HIGH TEMPERATURE CLIP 1100



Structure:

Very flexible ducting for temperatures up to + 1100°C

3 ply, Inside: high temperature stainless steel fabric,
Middle ply: high temperature isolation fabric, Outside:
PU- coated high temperature fabric, reinforced by woven
in stainless steel wire, silver-grey

Ø 76 to <100 - 2-hose-construction, from Ø > 100 - Standard

Temperature range:

-60°C up to 1100°C

Standard Length:

3 / 6 Meter

Properties:

Good temperature resistance, outer wear strip, flame retardant, excellent axial compressibility

Applications:

Spark extraction, suction of exhaust gases, flue gas extraction and suction of other hot fumes, gases or dust in all fields of industry

ID mm	Wall Thick. mm	Bending Radius mm	Vacuum bar
76	4	45	0.31
80	4	54	0.28
90	4	55	0.25
102	4	60	0.2
112	4	66	0.17
120	4	72	0.14
127	4	75	0.13
140	4	84	0.11
152	4	90	0.09
160	4	96	0.08
180	4	108	0.06
203	4	120	0.05
254	4	175	0.04
305	4	210	0.02
407	4	280	0.01
508	4	400	0.01
600	4	500	0.01



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002