



FLEXAFLEX HOSES INTERNATIONAL  
Ahmedabad



**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458



**Chirag Shah - Technical**  
+91-79903 36570



**S.D. Shah - Director**  
+91-90990 16044

## J 3-6 PVC FLEX SUPERELASTIC HOSE



### Properties:

- ★ Light model
- ★ Highly flexible
- ★ Good resistance to alkalis and acids
- ★ Good resistance to UV and ozone
- ★ Small bending radius
- ★ Kink-proof
- ★ Capable of electrostatic discharge (according to BGR 132, formerly ZH 1/200) by grounding the spiral  $\leq 106\Omega$

### Structure:

Wall: soft PVC with fibre reinforcement  
Spiral: plastic coated spring steel wire

### Material:

PVC coated fibre  
Spring steel wire

### Standard Color:

Black

### Temperature range:

-10°C approx. to + 85°C approx.

### Applications:

Suction and blast hose, especially suitable:

- ★ For solids such as dust, powder and fibre
- ★ For gaseous and liquid media
- ★ For domestic and industrial vacuum cleaners, building drying and welding gas extraction
- ★ Multi-purpose hose for the transport of air, liquids and solid materials; especially designed for floor care devices, vacuum cleaners and automatic scrubbers

ID mm	OD mm	Over pressure bar	Vacuum bar	Bending Radius mm	Weight kg/m	Std. Lengths meter
32	38	1.500	0.200	32	0.28	15
38	44	1.400	0.200	38	0.34	15
41	47	1.400	0.180	41	0.37	15
44	50	1.300	0.160	44	0.38	15
51	57	1.300	0.150	51	0.46	15
63	69	1.000	0.140	62	0.53	15
76	82	0.800	0.100	76	0.68	10
80	86	0.700	0.090	80	0.83	10
89	95	0.700	0.090	89	0.93	10
102	108	0.600	0.080	102	1.00	10



flexaflexhoses@gmail.com



www.flexaflexhoses.com  
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkuva Gate, Ahmedabad - 380 002