



FLEXAFLEX HOSES INTERNATIONAL  
Ahmedabad



**Pooja Shah - Sales**  
+91-99784 42215 | +91-70690 96458



**Chirag Shah - Technical**  
+91-79903 36570



**S.D. Shah - Director**  
+91-90990 16044

## J 6-4 PTFE AIR HOSE



### Structure:

PTFE mechanically clamped into metal band

Wall: PTFE coated fiberglass

Clamp profile: stainless steel

### Temperature range:

-70°C approx. to +250°C approx.

### Properties:

Light-weight

Kink-proof

**Anti-adhesive - Solvent Resistant.**

Small bending radius

**Axially compressible**

Strongly clamp into the wall

Odorless and tasteless

Good resistance to high temperature

Good resistance to alkalis,

Acids and chemicals

Good resistance to UV and ozone

**Flame-retardant according to UL94-V0**

### Applications:

For solids such as dust, powder, fibre and chip

For gaseous media such as vapors and smoke

For food and pharmaceutical industry

For chemical industry

ID mm	OD mm	Over pressure bar	Vacuum bar	Bending Radius mm	Weight kg/m	Std. Lengths meter
51	56	0.180	0.170	61	0.35	5
63	68	0.150	0.170	73	0.45	5
76	81	0.130	0.150	86	0.52	5
90	96	0.100	0.130	100	0.55	5
102	108	0.100	0.130	112	0.61	5
127	133	0.090	0.130	137	0.76	5
152	159	0.080	0.090	162	0.93	5
203	210	0.050	0.060	213	1.10	5
254	262	0.030	0.030	264	1.30	5
305	314	0.020	0.030	315	1.70	5



flexaflexhoses@gmail.com



www.flexaflexhoses.com  
www.hosesmarket.com



**FLEXAFLEX HOSES INTERNATIONAL**  
106, First Floor, Kailashpathi Chamber,  
Nr. Sunrise Restaurant, Reid Road,  
O/S Panchkva Gate, Ahmedabad - 380 002