



FLEXAFLEX HOSES INTERNATIONAL
Ahmedabad



Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458



Chirag Shah - Technical
+91-79903 36570



S.D. Shah - Director
+91-90990 16044

J 9-5 TPV EL AIR HOSE



Properties:

- ★ Super-light
- ★ Excellent compressibility 4:1
- ★ Good resistance to alkalis, acids, chemicals, UV and ozone
- ★ Flame-retardant according to UL94-HB
- ★ **Electrical and surface resistance**

Structure:

Spring steel wire integrated in wall
Fabric-reinforced wall

Material:

Wall: TPV coated fabric
Spiral: spring steel wire

Standard Color:

Black

Temperature range:

-20°C approx. to +150°C approx.

Wall Thickness:

0.5 mm

Applications:

Suction and blast hose, especially suitable:

- ★ **In areas liable to contain explosive mixtures (explosion protection)**
- ★ For welding gas extraction
- ★ For air conditioning and ventilation of fumes, light duty dust extraction and air movement

ID mm	OD mm	Over pressure bar	Vacuum bar	Std. Lengths meter
51	61	0.240	0.145	10
63	73	0.195	0.115	10
76	86	0.160	0.080	10
102	112	0.120	0.050	10
127	137	0.100	0.035	10
152	162	0.080	0.035	10
178	188	0.070	0.020	10
203	213	0.060	0.020	10
254	264	0.050	0.010	10
305	315	0.040	0.005	10
356	366	0.035	0.005	10
406	416	0.030	0.003	10



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002