



FLEXAFLEX HOSES INTERNATIONAL
Ahmedabad



Pooja Shah - Sales
+91-99784 42215 | +91-70690 96458



Chirag Shah - Technical
+91-79903 36570



S.D. Shah - Director
+91-90990 16044

J 9-6 EPDM EL HOSE



Structure:

Wall: EPDM

Spiral: PP

Standard Color:

Black

Temperature range:

-30°C approx. to +80°C approx.

Properties:

- ★ Conductive rubber material can be antistatic
- ★ Good resistance to sparking
- ★ Good resistance to alkalis and acids
- ★ Highly abrasion-proof
- ★ Smooth interior
- ★ **Flame-retardant according to UL94-V2**
- ★ **Electrical and surface resistance $\leq 10^6 \Omega$**

Applications:

- ★ **For area easy to burst mixtures such as dust, powder, fibre, chip and particles**
- ★ For gas and liquid environments, vacuum cleaners, conveying systems and compressors
- ★ For the electronics, chemical and other industries
- ★ Metal grinding machines for dust collection.

ID mm	OD mm	Pressure(MPa) Positive Pressure	Pressure(MPa) Negative Pressure	Weight kg/m	Std. Lengths meter
25	33	0.15	0.07	0.30	20
32	39	0.10	0.07	0.32	20
38	47	0.08	0.07	0.43	20
51	60	0.08	0.06	0.52	20
64	71	0.07	0.05	0.71	20
76	86	0.06	0.04	0.83	20
90	100	0.05	0.03	0.99	20
102	112	0.05	0.02	1.13	20



flexaflexhoses@gmail.com



www.flexaflexhoses.com
www.hosesmarket.com



FLEXAFLEX HOSES INTERNATIONAL
106, First Floor, Kailashpathi Chamber,
Nr. Sunrise Restaurant, Reid Road,
O/S Panchkuva Gate, Ahmedabad - 380 002